



# CD-401 3HWBSCOMA-HWTB

## HONDA GX390, 4000 PSI

POWERED by  
**HONDA**



THE **BE**  
COOL DRIVE FEATURE  
DRAWS COOL AIR INTO PULLEY AND KEEPS  
YOUR PUMP **25% COOLER**



### SPECIFICATIONS

PART#	GPM	PSI	DISPLACEMENT	TRIPLEX PUMP	UNLOADER
CD-4013HWBSCOMA-HWTB	3.5	4000	389cc HONDA GX390	COMET FW23540	BLOCK MOUNT

#### ACCESSORIES INCLUDED

PART #	DESCRIPTION
2X 85.238.156	3/8" 50' GREY NON MARKING HOSE
85.205.026	36" GUN/WAND/COUPLINGS
85.210.040BEP	#4 QUICK CONNECT NOZZLES: 0°, 15°, 40°, SOAPER
85.205.026	WAND ASSEMBLY WITH GUN AND COUPLER
85.206.018L	18" STANDARD FIBERGLASS TELESCOPING WAND
85.300.044	BALL VALVE KIT
85.403.007	20" WHIRL-A-WAY

STAINLESS STEEL FRAME

#### PUMP OPTIONS



COMET FW23540  
85.149.031B  
REPLACEMENT UNLOADER  
85.300.032



#### SHIPPING



27 IN



#### ADDITIONAL INFO

- LOW PRESSURE CHEMICAL INJECTOR
- STAINLESS STEEL FRAME **PART# 85.600.081**
- 13" PNEUMATIC TIRES **PART# 85.660.020**
- ENGINE OIL 10W 30 **PART# 85.490.002**
- PUMP OIL 30W NON DETERGENT **PART# 85.490.000**
- 1" KEYED SHAFT

ENGINE  
WARRANTY



PUMP  
WARRANTY

