

Commercial Power Washers

GENERAC®

Power Washers



3100 psi - Model 006590-0 (49-State & Canada)
UPC: 696471065909

Model 006607-0 (50-State)
UPC: 696471066074

3800 psi - Model 006564-0 (49-State & Canada)
UPC: 696471065640

4200 psi - Model 006565-0 (49-State & Canada)
UPC: 696471065657



*Built in the USA using domestic
and foreign parts

FEATURES

PRO-GRADE TRIPLEX PUMP

- Up to 4X longer life than axial cam pumps

POWERFUL GENERAC OHV ENGINE

- Delivers maximum cleaning performance and reliability

STEEL-REINFORCED HOSE

- Durable, non-marring hose will not leave scuff marks

FOLDING HANDLE

- For compact storage and transport

WELDED ROLL CAGE FRAME

- Protects components and provides gripping surfaces for easier lifting

BRASS QUICK CHANGE FITTINGS

- For faster connections

PRESSURE CONTROL VALVE

- For adjustable cleaning power

PROFESSIONAL SPRAY GUN

- Quick change connections, stabilizing side handle, molded grip, and easier-to-pull trigger for comfort during prolonged use

3100 • 3800 • 4200 psi
specifications
PRESSURE AND FLOW

Max Outlet Pressure (psi/bar)	3100/213 - 006590-0 & 006607-0 3800/262 - 006564-0 4200/290 - 006565-0
Max Flow Rate (gpm)/(L/min)	2.8/10.6 - 3100 psi 3.6/13.6 - 3800 psi 4.0/15.1 - 4200 psi

ENGINE

Manufacturer	Generac
Displacement (in ³ /cc)	12.9/212 - 3100 psi 18.4/302 - 3800 psi 25.6/420 - 4200 psi
Type	OHV (Overhead Valve)
Orientation	Horizontal
Low Oil Shutdown System	Yes
Fuel Capacity (gal/L)	0.8/3 - 3100 psi 1.5/5.7 - 3800 psi 1.6/6.1 - 4200psi
Fuel On/Off Switch	Yes
Oil Capacity (oz/L)	20/0.6 - 3100 psi 37/1.1 - 3800 & 4200 psi
Recommended Engine Oil	SAE 30 or 10W30
Throttle Control	Manual
Choke	Manual
Starting Method	Manual/Recoil

PUMP

Type	Triplex
Plunger	Ceramic-coated stainless steel
Maximum Water Supply Temperature (°F/°C)	100/38

HOSE

Length (ft/m)	35/10.7 - 3100 & 3800 psi 50/15.2 - 4200 psi
Rating (psi/bar)	4000/276 - 3100 & 3800 psi 4200/290 - 4200 psi
Connectors	Quick change

NOZZLES

Number of Nozzles per Unit	5
Nozzle Descriptions	0, 15, 25, 40, soap

GUN & LANCE

Gun Type	Professional
Gun to Lance Connection	Quick Change
Gun to Hose Connection	Quick Change
Lance Length (in/cm)	20/51 - 3100 psi 33/84 - 3800 & 4200 psi
Lance to Nozzle Connection	Quick change

FRAME & MISC.

Handle	Folding
Frame Construction	Welded steel
Wheels (in/cm)	3 x 10/7.6 x 25.4 Never flat - 3100 & 3800 psi 4 x 12/10.2 x 30.5 pneumatic - 4200 psi

DIMENSIONS & WEIGHTS

Length (in/cm)	31.8/80.6 - 3100 psi 34.5/87.6 - 3800 & 4200 psi
Width (wheel to wheel, in/cm)	24.3/61.6 - 3100 psi 26.8/67.9 - 3800 psi 28.3/71.8 - 4200 psi
Height (in/cm)	38/96.5 - 3100 psi 42.5/108 - 3800 & 4200 psi
Unit Weight (lbs/kg)	102.5/46.5 - 3100 psi 129/58.5 - 3800 psi 146.5/66.5 - 4200 psi
Boxed Length (in/cm)	26/66 - 3100 psi 29/73.7 - 3800 & 4200 psi
Boxed Width (in/cm)	25.5/64.8 - 3100 psi 28/71.1 - 3800 & 4200 psi
Boxed Height (in/cm)	31/78.7 - 3100 psi 33.5/85.1 - 3800 & 4200 psi
Boxed Weight (lbs/kg)	120/54.4 - 3100 psi 150/68 - 3800 psi 164/74.4 - 4200 psi

WARRANTY

Warranty	3 year limited
----------	----------------