SPRAY GUNS & LANCE COMBINATIONS

GENERAL PUMP ®

REAR ENTRY SPRAY GUNS

DCG5010

DCG5010HE

DG4000

DG5010

DGE5010

DGE5010SL

DGE4012NT

DG4512

REAR ENTRY SPRAY GUNS						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
DCG5010	Compensating	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
DCG5010HE	Hydro Excacating	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
DG4000	Standard	8.0 GPM	4,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
DG5010	Standard	10.0 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
DGE5010	Standard	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
DGE5010SL	Locking Trigger	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
DGE4012NT	No Trigger	12.0 GPM	4,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
DG4512	Standard	12.0 GPM	4,500 PSI	3/8” NPT-F	1/4” NPT-F	320° F

REAR ENTRY SPRAY GUNS

YG5000

YG4000

YG4010

YRL56

YRL51

REAR ENTRY SPRAY GUNS						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
YG5000	Standard	10.0 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YG4000	Standard	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YG4010	Standard	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YRL56	Compensating	8.0 GPM	5,650 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YRL51	Compensating	13.2 GPM	4,050 PSI	3/8” NPT-F	1/4” NPT-F	320° F

STRAIGHT REAR ENTRY SPRAY GUNS

DG5000S

YG4500S

YG2527S

YG4032S

STRAIGHT REAR ENTRY SPRAY GUNS						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
DG5000S	Straight	8.0 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	300° F
YG4500SW	Straight/Weep	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	300° F
YG4500S	Straight	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	300° F
YG4500ST	Straight, SS Inlet	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	300° F
YG2527S	Straight	27.0 GPM	2,500 PSI	1/2” NPT-F	1/2” NPT-F	320° F
YG4032S	Straight	32.0 GPM	4,050 PSI	1/2” NPT-F	1/2” NPT-F	320° F

FRONT ENTRY SPRAY GUNS

DG2200

YRL20

ZGP11

FRONT ENTRY SPRAY GUNS					
Model	**GPM**	**MAX**	**INLET**	**OUTLET**	**MAX TEMP**
DG2200	6.5 GPM	1,800 PSI	3/8” NTP-F	1/4” NTP-F	185° F
YRL20	8.0 GPM	3,200 PSI	3/8” BSP-F	1/4” BSP-F	320° F
ZGP11	10.5 GPM	3,000 PSI	3/8” BSP-F	1/4” BSP-F	285° F

HIGH FLOW REAR ENTRY WASH DOWN SPRAY GUNS

YG1635

YG1635SR

HIGH FLOW REAR ENTRY WASH DOWN SPRAY GUNS						
MODEL	**DESCRIPTION**	**GPM**	**MAX**	**INLET**	**OUTLET**	**MAX TEMP**
YG1635	Wash Down	16.0 GPM	350 PSI	1/2” BSP-F	Adj. Cone Nozzle	195° F
YG1635N	Wash Down	16.0 GPM	350 PSI	1/2” NPT-F	Adj. Cone Nozzle	195° F
YG1635S	Wash Down W/Swivel	16.0 GPM	350 PSI	1/2” BSP-F	Adj. Cone Nozzle	195° F
YG1635SR	Wash Down W/Swivel, SS Pin	16.0 GPM	350 PSI	1/2” BSP-F	Adj. Cone Nozzle	195° F
YG1635SS	Wash Down W/Swivel, 316 SS	16.0 GPM	350 PSI	1/2” BSP-F	Adj. Cone Nozzle	195° F
YG2635AS	Wash Down W/Swivel	26.5 GPM	350 PSI	1/2” BSP-F	Adj. Cone Nozzle	195° F

REAR ENTRY SPRAY GUNS - WITH CERAMIC BALL

REAR ENTRY SPRAY GUNS - CERAMIC BALL						
MODEL	**DESCRIPTION**	**GPM**	**MAX**	**INLET**	**OUTLET**	**MAX TEMP**
YG5000C	Ceramic Ball	10.0 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YG5000CS	Ceramic Ball and SS I/O	10.0 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YG4500STC	Ceramic Ball / Straight	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	300° F

REAR ENTRY SPRAY GUNS - WEEP

REAR ENTRY SPRAY GUNS - WEEP						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
YG5000W	Standard	10.0 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YG4010SW	Swivel	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YG4000WN	Standard	10.5 GPM	4,050 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YRL2640W	Standard	8.0 GPM	4,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
DG4000W	Standard	8.0 GPM	4,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
DG5010W	Standard	10.0 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
DGE4012W	Standard	12.0 GPM	4,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F

REAR ENTRY SPRAY GUNS STAINLESS STEEL

REAR ENTRY SPRAY GUNS - STAINLESS STEEL						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
YG1732	Cartridge	32.0 GPM	1,950 PSI	1/2” BSP-F	1/2” BSP-F	210° F
YG2953B	Cartridge	53.0 GPM	3,200 PSI	3/4” BSP-F	1/2” BSP-F	210° F
YG4060SS	Blue	10.5 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YG5200	Red	10.5 GPM	6,400 PSI	3/8” NPT-F	1/4” NPT-F	320° F
YG7207	Compensating	7.5 GPM	8,000 PSI	3/8” NPT-F	1/4” NPT-F	320° F

SPRAY GUN
LANCE COMBINATIONS

2100457

YG34LA27

YG29LA31

YRL56L


Y30256717


101002

SPRAY GUN / LANCE COMBINATIONS						
MODEL	DESCRIPTION	GPM	MAX	INLET	OUTLET	MAX TEMP
2100457	Locking, Dual Tr., 48” Lance	10.2 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	250° F
2100457L69	Locking, Dual Tr., 69” Lance	10.2 GPM	5,000 PSI	3/8” NPT-F	1/4” NPT-F	250° F
YG3000DS	16” Lance	10.5 GPM	3,050 GPM	3/8” NPT-F	1/8” NPT-F	140° F
YG3000D	40” Lance	10.5 GPM	3,050 GPM	3/8” NPT-F	1/8” NPT-F	140° F
YG34LA27	Gun, 27” Adjustable Lance, 3.5 mm Nozzle, 21.0 GPM					
YG29LA31	Gun, 31.5” Adjustable Lance, 2.3 mm Nozzle, 8.0 GPM					
YG5200/L42	YG5200 with Stainless Steel Lance					
YRL56L	42” Lance	8.0 GPM	5,650 PSI	3/8” NPT-F	1/4” NPT-F	320° F
Y30256717	YG5000 Assembled with 36” Lance and 1/4” Quick Disconnect					
100751	YG5000 Assembled with 18” Lance and 1/4” Quick Disconnect					
100059	YG4010 Assembled with 36” Lance and 1/4” Quick Disconnect					
101002	YG7207 Spray Gun with 36” Stainless Steel Lance, 7.5 GPM, 7,250 PSI					
100160	DG5010 Assembled with 36” Vented Lance and 1/4” Quick Disconnect					
101057	DG5010 Assembled with 36” Insulated Lance and 1/4” Quick Disconnect					
101096	DG5010 Assembled with 48” Vented Lance and 1/4” Quick Disconnect					
101109	DGE5010 Assembled with 24” Insulated Lance and 1/4” Quick Disconnect					
101110	DGE5010 Assembled with 36” Insulated Lance and 1/4” Quick Disconnect					
2100260	DG4000 Assembled with 36” Insullated Lance and 1/4” Quick Disconnect and 3/8” Plug Inlet, 8 GPM, 4000 PSI					

GENERAL PUMP

GP Companies, Inc
1174 Northland Drive, Mendota Heights, MN 55120
Phone: 651.686.2199 Fax: 800.535.1745
www.generalpump.com email: sales@gpcompanies.com
facebook.com/gpcompanies

General Pump is part of the Interpump Group, the world leader in plunger pumps.