

Pumps (General Pump & EK pumps)

- Commercial Duty Triplex Plunger Pumps
- Oil Bath Crank Case • Stainless Valves
- Brass Manifold • Direct Drive
- Thermo Pump Protector

Electric Motors (2, 5 & 7.5 HP)

- 1750 RPM • TEFC • Full Frame
- 1.15 Service Factor
- Thermal Overload Protection
- Continuous Duty

Electrical Control Panel

- Nema 4 • Water Tight • Easy Access
- Heavy Duty On / Off Cam Switch or
Optional Auto Stop / Start with
Time Delay

Heating Coil

- Schedule 80 Pipe
- Elliptically Wound & Stretched
- No Seam Welds
- Structurally Braced to Reduce Vibration &
Pipe Wear • Sealed with Ceramic Blanket
- Stainless Steel Housing

Burners

- Oil Fired • Adjustable Thermostat
- On/Off Switch • North American Made
- Dependable • Serviceable

Frame

- All Welded • Powder Coated
- 12 Gauge Bent Steel Roll Cage • Lifting Bar
- 3/4" Threaded Axles Welded to Frame
- 13" Pneumatic Wheels Attached with Lock
Nuts • 10 Gallon Poly Fuel Tank
- Hose Reel Mounting Plate

Includes

- 36" Gun and Wand Assembly with Quick
Coupler System • 0°/15°/25°/40° Nozzles
- 1 Soap Nozzle • Downstream Chemical
Injection System • 50 Feet of High Pressure
Hose

Options & Accessories

- Auto Stop/Start • Hose Reel
- Rotary Nozzle • Wet Sandblast Kit
- Water Broom • Drain Cleaning/Jetter Kit • For Propane Fired Units (EZP)

Dependable, long lasting machines built for a multitude of applications. Heats water faster and hotter than our competitors.



EZO1520E with
Optional Auto
Stop/Start

EZO2435E-GP with
Optional Auto Stop Start
& Hose Reel



MODEL	GPM	PSI	BTU	ELECTRIC DRIVE	HP/VOLTAGE
EZO1520E	2	1500	200,000	1750 RPM	2/110V/1ph *
EZO2434E	3.4	2400	350,000	1750 RPM	5/220V/1ph
EZO2435E-GP	3.5	2400	350,000	1750 RPM	5/220V/1ph *
EZO3636E	3.6	3600	350,000	1750 RPM	7.5/220V/1ph
EZO3035E-GP	3.5	3000	350,000	1750 RPM	7.5/220V/1ph *