

COMMERCIAL & HOME MAINTENANCE

Airless Paint Sprayer
PS261C / PS260F



EASY to MAINTAIN

Diaphragm Pump with long life cartridge valves make maintenance quick and easy. Comes with solid aluminum block construction with high quality brass fittings and a lifetime warranty on diaphragm.



EASY to CONTROL

Ergonomic spray gun built with Quadraflow tip for precise spray pattern, less clogging and less overspray. Contractor tested for comfortable, long term use. Includes spray gun with .015 in. (0,38 mm) tip and 25 ft. (7,62 m) high pressure airless hose.
[Model PS260F includes 50 ft.

(15,2 m) of hose.]



EASY to START

Flexible suction assembly, is equipped with prime booster to get started quickly. Large suction filter extends valve and tip life. Works with 1 or 5 gallon (4 or 19 liter) buckets.



EASY to USE

TEFC electric motor includes totally enclosed fan cooled design for safe operation. Power to spray a variety of coatings: oil-based stain, latex, oil-based paint. Lifetime Warranty.



EASY to MOVE

Heavy-duty fold-down frame with large wheels designed for easy portability. Integrated rack easily manages 75 ft. of hose. Attached hook for 5 gallon buckets

SPECIFICATIONS

 HORSEPOWER
 3/4
 GPM
 0.34 (1,28)*
 PS261C
 60 Hz / 110/120V

 MAX HOSE
 150 ft. (45,7 m)
 MAX TIP
 .017 in. (0,43 mm)
 PS260F
 50Hz & 60Hz/ 220/240V

PS261C Carton: 24.5"L/20.25"W/24.75"H Carton Weight: 60.5 lbs. UPC: 045564 62099-8

PS260F Carton: 25.25"L/21"W/26.63"H Carton Weight: 64.5 lbs. UPC: 045564 61369-3

*Flow rate @ 2000 psi (137,9 Bar)





chpower.com