

Cam Spray Model UV3030H-HOT Trailer Mount Hot Water Pressure Washer

HOT WATER SPECIFICATIONS

- Triplex plunger pump with ceramic plungers and stainless steel valves
- Adjustable thermostat
- Pressure pop-off
- Chemical injection
- Industrial painted 1 inch square steel tube frame (U.S. Manufactured)
- Easily replaceable schedule 80 coil with stainless cold wrap (U.S. manufactured)
- Unit is a skid style; no electricity required, equipped with a 12 volt oil fired burner
- Group 24 Battery included
- Unit can be operated as either a cold water only or hot water unit
- Assembled in USA
- **All hot water machines must be properly vented if operated indoors**



TRAILER SPECIFICATIONS

- Trailer has full diamond plate deck; powder coated frame with 13" wheels, 2000# axle, road ready lights and wiring
- 150 gallon water tank with auto shut off float (shuts machine down when dry)
- 2 manual hose reels; one with 100' pressure hose and one with 150' garden hose mounted on back toolbox

Product Specifications:

- Operating Pressure in psi/bar : 3000 / 207
- Flow Rate in gmp/lpm : 3 / 11.4
- Engine Displacement: 270 cc
- Engine Manufacturer: Honda GX Recoil
- Engine Fuel Tank Capacity: 6.9 quart
- Maximum Pump Inlet Water Temperature : 140° F
- Hose Dimension : 100' x 3/8"
- Gun/Wand/Tip: Trigger gun/dual wand with side handle and detergent tip with interchangeable pressure nozzles in 0°, 15°, 25° and 40°
- Burner Fuel Tank Capacity : 9 gallon
- Burner Fuel Type : #1, #2 Diesel, Kerosene or JP8
- Product Dimension: 132" x 60" x 48"
- Ship Weight : 1300 lbs.

Cam Spray • 520 Brooks • Iowa Falls, IA 50126

Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com