

Cam Spray Model 4040EWMA Wall Mount Series Electric Pressure Washer

- Triplex plunger pump with ceramic plungers and stainless steel valves
- Chemical Injection
- Heavy duty totally enclosed fan cooled motor
- Powder coat painted wall mount bracket
- Equipped with auto start/stop system
- Unlike most auto start/stop systems, Cam Spray uses a flow switch with a pilot circuit as the triggering mechanism. When you power on the machine you manually push the start button. The first time you squeeze the trigger the pilot circuit senses the water flow and starts the motor. When the gun is released the flow stops and the flow switch then triggers a timer that starts counting down from 15 seconds. If the gun is pulled to start washing again with the count-down period the motor will continue to operate. If not the machine will shut down until the gun is pulled again. This unique feature greatly reduces motor problems related to rapid starting and stopping of the motor every time the gun is triggered.
-
- Look for accessories like the wall mount swivel hose reels
- Assembled in USA



Product Specifications:

- Operating Pressure in psi/bar : 4000 / 276
- Flow Rate in gpm/lpm : 4 / 15.2
- Horsepower : 10
- Voltage/Amperage/Phase : 230 volt / 40 Amp / 1 ph
- Power Cord : 10'
- Maximum Pump Inlet Water Temperature : 160° F
- Pump Thermal Protection : Mechanical
- Hose Dimension : 50' x 3/8"
- Gun/Wand/Tip: Trigger gun/36" wand with interchangeable tips in 0°, 15°, 25° 40° pressure nozzles and soap tip
- Product Dimension: 28" L x 22" W x 30" H
- Ship Weight : 300 lbs.

Cam Spray • 520 Brooks • Iowa Falls, IA 50126

Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com