



Cam Spray Electric Powered Portable Sewer and Drain Jetter

Quantity:

[SW4004E]

[Request a Quote](#)

- Direct Drive Triplex plunger pump with ceramic plungers and stainless steel valves.
- 35' power cord
- **10 h.p. Industrial Electric motor is single phase and operates of 230 Volt 50 amp service. (3 Phase Available)**
- **200' x 3/8" hose on manual reel.**
- Power pulse feature
- Adjustable pressure
- Pressure gauge
- Chemical Injection
- 75' x 1/8" trap hose
- Clear 80 mesh strainer
- Pumps handle fluids up to 160° degrees
- Powder coat frame
- pneumatic tires with tube
- Tool Box with gloves, face shield, 4 nozzle assortment with cleaning tool and backflow preventor
- Fixed Manual Reel with shut off valve
- Weighs 425 lbs.
- Measures 54" long, 29" wide and 40" high

Product Features:

- Product Dimensions : 54" x 29" x 40"
- Voltage/ Amperage/ Phase : 230 Volt / 50 Amp / 1
- Horsepower : 10
- Operating Pressure in psi/ bar : 4000 / 276
- Flow Rate in gpm/ lpm : 4 / 15.2
- Pump Thermal Protection : Mechanical
- Maximum Pump Inlet Water Temperature : 160 degrees F
- Hose Dimension : 200' x 3/8"
- Jetter Hose Reel Type : Manual
- Power Cord : 35'

[Commercial Pressure Washers](#) | [Cold Water Electric Pressure Washers](#) | [Drain & Sewer Jetters](#) | [Trailer Mounted Sewer Jetters](#) | [Water Pumps](#) | [Misting Systems](#) | [Contact Us](#)

Cam Spray • 520 Brooks Road • Iowa Falls, IA 50126
Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com
[Site Map](#) | [Privacy Policy](#) | Site Credits: [Ecreativeworks](#)