

Cam Spray Model 1502WM/SSA Wall Mount Series Electric Pressure Washer

- Triplex plunger pump with ceramic plungers and stainless steel valves
- Auto start/stop feature built into the pump
- Adjustable pressure
- Adjustable dual chemical injection with 10' chemical hoses
- Heavy duty totally enclosed fan cooled motor (U.S. manufactured)
- Stainless Steel frame with wand/hose rack
- Assembled in USA



Product Specifications:

- Operating Pressure in psi/bar : 1500 / 103.5
- Flow Rate in gpm/lpm : 2 / 7.6
- Horsepower : 2
- Voltage/Amperage/Phase : 120 volt / 20 Amp / 1 ph
- Power Cord : 35' with GFCI
- Maximum Pump Inlet Water Temperature : 160° F
- Pump Thermal Protection : Mechanical
- Hose Dimension : 50' x 3/8"
- Gun/Wand/Tip: Trigger gun with 36" wand and interchangeable pressure nozzles in 0°, 15°, 25°, 40° and soap tip
- Product Dimension: 23" L x 16" W x 31" H
- Ship Weight : 165 lbs.

Cam Spray • 520 Brooks • Iowa Falls, IA 50126

Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com