

# Cam Spray Model CBG7042HT Trailer Mount Hot Water Pressure Washer

## HOT WATER SPECIFICATIONS

- Gearbox driven triplex plunger pump with ceramic plungers and stainless steel valves
- Adjustable pressure
- Adjustable thermostat
- Pressure pop-off
- Chemical injection standard on 3000-5000 PSI models
- Easily replaceable schedule 80 coil with stainless cold wrap (U.S. manufactured)
- Unit is a skid style; 12 volt burner system
- Group 24 Battery included
- Unit can be operated as either a cold water only or hot water unit
- Assembled in USA
- **All hot water machines must be properly vented if operated indoors**



## TRAILER SPECIFICATIONS

- Trailer has full diamond plate deck; powder coated frame with 15" wheels, tandem 3500# axles, road ready lights and wiring and brakes
- 300 gallon water tank with auto shut off float (shuts machine down when dry)
- 2 manual hose reels; one with 100' pressure hose and one with 150' garden hose mounted on back toolbox

## Product Specifications:

- Operating Pressure in psi/bar : 7000 / 483
- Flow Rate in gpm/lpm : 4/ 15.1
- Engine Displacement: 688 cc
- Engine Manufacturer: Honda GX Electric Start
- Engine Fuel Tank Capacity: 5 gallon
- Maximum Pump Inlet Water Temperature : 140° F
- Pump Thermal Protection: Mechanical
- Hose Dimension : 100' x 3/8"
- Gun/Wand/Tip: Trigger gun/48" wand and interchangeable pressure nozzles in 0° and 15°
- Burner Fuel Type : #1, #2 Diesel, Kerosene or JP8
- Burner Fuel Tank Capacity : 9 gallon
- Water Tank Capacity: 300 gallons
- Product Dimension: 186" L x 74" W x 72" H
- Ship Weight : 2500 lbs.

Cam Spray • 520 Brooks • Iowa Falls, IA 50126

Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: [sales@camspray.com](mailto:sales@camspray.com)