Cam Spray MX Series Electric Pressure Washer

- Triplex plunger pump with ceramic plungers and stainless steel valves.
- 35' power cord with GFCI
- Adjustable pressure
- Dual Chemical Injection, frame will hold 2, 1 gallon containers of your chemical and control valve will adjust to choose the chemical and vary the injection rate.
- Trigger Gun
- 36" two piece wand
- Totally enclosed heavy duty motor
- Pumps will handle fluids up to 140° degrees fahrenheit
- 10" Pneaumatic tires with tubes.
- Powder Coated Metal Frame with hose and wand holder and accessory reel mounting bracket.
- This model is CETL approved to UL 1776 specifications.



• Product Dimensions: 32" x 22" x 39"

Voltage/Amperage/Phase: 120 Volt / 15 amp / 1

• Horsepower: 1.5

• Operating Pressure in psi/bar: 1000 / 69

• Flow Rate in gpm/lpm: 2.2 / 8.4

• Pump Thermal Protection : Mechanical

Maximum Pump Inlet Water Temperature : 140° F

Hose Dimension : 50' X 3/8"Power Cord : 35' with GFCI

Cam Spray • 520 Brooks Road • Iowa Falls, IA 50126

Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com

