Cam Spray Model 1000SHDE SH Series Oil Fired Hot Water Pressure Washer

- Triplex plunger pump with ceramic plungers and stainless steel valves.
- Adjustable pressure
- Adjustable Thermostat and pressure pop-off
- Chemical Injection
- Trigger Gun
- Dual wand with side handle and detergent tip
- Quick change tips in 0°,15°,25° and 40°
- Totally enclosed motor
- · Powder coated frame with wand/hose rack
- 13" pneumatic tires with tube
- Schedule 80 coil with stainless cold wrap
- Rust free burner fuel tank
- \bullet Oil fired burner uses diesel fuel or kerosene to achieve a 140° fahrenheit rise in water temperature
- Look for optional accessories like the swivel hose reel that mounts to the frame
- All hot water machines must be properly vented if operated indoors.



• Product Dimensions: 34" x 27" x 47"

Voltage/Amperage/Phase : 120 Volt / 20 Amp/ 1

• Horsepower: 2

Operating Pressure in psi/bar: 1000 / 69

Flow Rate in gpm/lpm: 3 / 11.4

• Pump Thermal Protection : Mechanical

Maximum Pump Inlet Water Temperature: 140° F

• Hose Dimension: 50' X 3/8"

• Burner Fuel Tank Capacity : 5 Gallon

• Burner Fuel Type: #1, #2 Diesel or Kerosene

• Power Cord: 35' with GFCI

Cam Spray • 520 Brooks Road • Iowa Falls, IA 50126

Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com

