Cam Spray Model CBG5055HT Trailer Mount Hot Water Pressure Washer

- Triplex plunger pump with ceramic plungers and stainless steel valves.
- Adjustable pressure
- Adjustable Thermostat and pressure pop-off
- Chemical Injection
- Hose reel with 150' of garden hose for tank fill
- Trigger Gun
- Dual wand with side handle and detergent tip
- Hose Reel with 100' pressure wash hose
- Quick change tips in 0°,15°,25° and 40°
- · Powder coat frame and trailer
- · Roto-molded tank with automatic shut-off if machine runs dry
- Trailer has lights and is road ready with 15" wheels, tandem 3500# axles and brakes
- Schedule 160 coil with stainless cold wrap
- Oil fired burner uses diesel fuel or kerosene to achieve a 140° fahrenheit rise in water temperature
- 2500 watt generator system
- Industrial Electric Start Engine w/Hour Meter
- 9 gallon rust free Diesel/Kerosene Tank
- 5 Gallon Gasoline/Unleaded Fuel Tank

Products Features:

Product Dimensions: 186" x 74" x 72"

• Engine Manufacturer : Honda E/S

• Horsepower : 688 cc

• Operating Pressure in psi/bar: 5000 / 345

Flow Rate in gpm/lpm: 5.5 / 20.9

• Pump Thermal Protection: Mechanical

Maximum Pump Inlet Water Temperature : 140° F

• Hose Dimension: 100' X 3/8"

• Engine Fuel Tank Capacity: 9 Gallon

• Burner Fuel Tank Capacity: 9 Gallon

• Burner Fuel Type: #1, #2 Diesel or Kerosene

• Water Tank Capacity in U.S. Gallons: 300 Gallon

Cam Spray • 520 Brooks Road • Iowa Falls, IA 50126

Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com

