

# Cam Spray MX Series Electric Pressure Washer

- Triplex plunger pump with ceramic plungers and stainless steel valves.
- 35' power cord with GFCI
- Adjustable pressure
- Dual Chemical Injection, frame will hold 2, 1 gallon containers of your chemical and control valve will adjust to choose the chemical and vary the injection rate.
- Trigger Gun
- 36" two piece wand
- Totally enclosed heavy duty motor
- Pump will handle water up to 160° degrees fahrenheit
- 10" Pneumatic tires with tubes.
- Powder Coated Metal Frame with hose and wand holder and accessory reel mounting bracket.
- This model is CETL approved to UL 1776 specifications.



## Products Features:

- Product Dimensions : 32" x 22" x 39"
- Voltage/Amperage/Phase : 120 Volt / 15 amp / 1
- Horsepower : 1.5
- Operating Pressure in psi/bar : 1000 / 69
- Flow Rate in gpm/lpm : 2.2 / 8.4
- Pump Thermal Protection : Mechanical
- Maximum Pump Inlet Water Temperature : 160° F
- Hose Dimension : 50' X 3/8"
- Power Cord : 35' with GFCI

Cam Spray • 520 Brooks Road • Iowa Falls, IA 50126  
Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: [sales@camspray.com](mailto:sales@camspray.com)