GENERAC®

Residential **Power Washers**

Power Washers





2000 - 3000 psi - Model 006809-0 (50-State CARB Compliant) UPC: 696471068092



FEATURES

POWERFUL GENERAC OHV ENGINE

• Delivers maximum cleaning performance and reliability

AXIAL CAM PUMP WITH EASY-ACCESS HOSE CONNECTIONS

· Prevents kneeling down on the ground

ERGONOMIC SPRAY GUN

 Molded grip, easier-to-pull trigger, and rear hose connection for comfort during prolonged use

OVERSIZED NEVER-FLAT TIRES

· Improved mobility on rugged terrain

QUICK CLICK NOZZLE TIPS

· Easily change the intensity of the spray to suit the application

COMPACT DESIGN

 Minimum storage space required in the garage or shed

POWERDIAL™ VARIABLE PRESSURE CONTROL

· Adjust the spray intensity to meet a wide variety of cleaning tasks

GENERAC°

2000 - 3000 psi

Specifications

PRESSURE AND FLOW

Max Outlet Pressure (psi/bar)	3000/207
Max Flow Rate (gpm)/(L/min)	2.5/9.5

ENGINE

Displacement (in³/cc) 12.9/212 Type OHV (Overhead Valve) Orientation Horizontal Low Oil Shutdown System No Fuel Capacity (qt/L) 0.8/3		
Type OHV (Overhead Valve) Orientation Horizontal Low Oil Shutdown System No Fuel Capacity (qt/L) 0.8/3 Fuel On/Off Switch Yes Oil Capacity (oz/L) 20/0.6 Recommended Engine Oil SAE 30 or 10W30 Throttle Control PowerDial™ / Manual Choke Manual	Manufacturer	Generac
Orientation Horizontal Low Oil Shutdown System No Fuel Capacity (qt/L) 0.8/3 Fuel On/Off Switch Yes Oil Capacity (oz/L) 20/0.6 Recommended Engine Oil SAE 30 or 10W30 Throttle Control PowerDial™ / Manual Choke Manual	Displacement (in ³ /cc)	12.9/212
Low Oil Shutdown System No Fuel Capacity (qt/L) 0.8/3 Fuel On/Off Switch Yes Oil Capacity (oz/L) 20/0.6 Recommended Engine Oil SAE 30 or 10W30 Throttle Control PowerDial™ / Manual Choke Manual	Туре	OHV (Overhead Valve)
Fuel Capacity (qt/L) Fuel On/Off Switch Oil Capacity (oz/L) Recommended Engine Oil Throttle Control Choke Oil Capacity (oz/L) PowerDial™ / Manual	Orientation	Horizontal
Fuel On/Off Switch Yes Oil Capacity (oz/L) 20/0.6 Recommended Engine Oil SAE 30 or 10W30 Throttle Control PowerDial™ / Manual Choke Manual	Low Oil Shutdown System	No
Oil Capacity (oz/L) 20/0.6 Recommended Engine Oil SAE 30 or 10W30 Throttle Control PowerDial™ / Manual Choke Manual	Fuel Capacity (qt/L)	0.8/3
Recommended Engine Oil SAE 30 or 10W30 Throttle Control PowerDial™ / Manual Choke Manual	Fuel On/Off Switch	Yes
Throttle Control PowerDial™ / Manual Choke Manual	Oil Capacity (oz/L)	20/0.6
Choke Manual	Recommended Engine Oil	SAE 30 or 10W30
	Throttle Control	PowerDial™ / Manual
Starting Method Manual/Recoil	Choke	Manual
	Starting Method	Manual/Recoil

PUMP

Туре	Axial cam
Maximum Water Supply Temperature (°F/°C)	100/38

HOSE

Length (ft/m)	25/7.6
Diameter (in/mm)	.25/6.35
Rating (psi/bar)	3100/214
Connectors	M22 threaded

DETERGENT SYSTEM

Chemical Description	Siphon hose

NOZZLES

Number of Nozzles per Unit	3
Nozzle Descriptions	0, 25, Soap

GUN & LANCE

Gun Type	Ergonomic
Gun to Lance Connection	M22 Threaded
Gun to Hose Connection	M22 Threaded
Lance Length (in/cm)	20/51
Lance to Nozzle Connection	Quick change

FRAME & MISC.

Handle	Folding
Frame Construction	Welded steel
Wheels (in/cm)	1.75 x 10/3.8 x 25.4 Never flat

DIMENSIONS & WEIGHTS

Length (in/cm)	20.6/52.3
Width (wheel to wheel, in/cm)	18.5/47
Height (in/cm)	39/99.1
Unit Weight (lbs/kg)	68/30.8
Boxed Length (in/cm)	22.4/56.9
Boxed Width (in/cm)	20/50.8
Boxed Height (in/cm)	23.1/58.7
Boxed Weight (lb/kg)	76/34.5

WARRANTY

Warranty	2 year limited
----------	----------------

