1/2" NPT-F 1/2" NPT-F

250° F




SPECIFICATIONS PART NUMBER DHRA50150 DHRA50300 DHRA50450 3/8" Hose Capacity 150 ft. 300 ft. 450 ft. 5/8" Garden Hose Cap. 125 ft. 225 ft. 325 ft. 3/4" Garden Hose Cap. 100 ft. 175 ft. 250 ft. Swivel Pressure Rating 5,000 PSI

FEATURES / BENEFITS

- Friction Brake
- Direct hand-crank rewind with locking pin
- Solid steel construction
- Durable powdercoated finish
- Full flow swivel stainless swivel

DIMENSIONS




Inlet

Outlet

Max. Temp

	Dimensions inches/mm						
	Α	В	C	D	E	F	G
DHRA50150	17.7/450	15.2/387	18.6/473.6	12.4/315	10.4/264	7.7/196	22.0/558
DHRA50300	17,7/450	15.2/387	18.6/473.6	17.5/445	15.5/394	12.8/326	27.0/688
DHRA50450	17.7/450	15.2/387	18.6473.6	23.0/585	21.2/539	18.3466	32.6/829









DHRA50150/300/450

Industrial Hose Reels

PARTS LIST


Item	Part No.	Description	QTY
	2103282	Assy, Hub & Flange, DHRA50450	
1	2103242	Assy, Hub & Flange, DHRA50300	1
	2103247	Assy, Hub & Flange, DHRA50150	
	2103283	Frame, Hose Reel, DHRA50450	
2	2103243		
	2103248		
3	2640025	Pillow Block	2
4	2103244	Assy, Crank	1
5	2103245	Assy, Lock Pin	1
6	2540087	Bracket, Brake	1
7	2660268	Brake	1
8	2200103	Bolt, M8	1
9	2203413	Washer, Flat, M10	12
10	2660405	Knob, Brake	
11	2203017	Nut, M10, Nylok, SST	
12	2200013	Washer, M8, SS	
13	DSW9012SS	Swivel 1/2" NPT-F Ball Bearing	1
14	2530112	Fitting, 1/2NPT-MX3/8NPT-F	2
15	2200104	Bolt, M10	6
16	D10032K	Fitting, GH-F 1/2" NPT-M, Filter & Spring	1





Lock Pin Repair Kit 2103245					
Item	Part No.	Description	QTY.		
1	2540085	Bracket, Lock	1		
2	2540086	Pin, Lock	1		
3	2720025	Spring, Lock Pin	1		
4	2200013	Washer, M8, SS	1		
5	2202033	Pin, Cotter, 2x20	1		

	Brake Repair Kit 2103139				
Item	Part No.	Description	QTY.		
1	2660268	Brake	1		
2	2200103	Bolt, M8	1		
3	2660405	Knob, Brake	1		
4	2200013	Washer, M8, SS	1		



ASSEMBLY / OPERATING INSTRUCTIONS

- 1. Connect the handle to either end of the axle which doubles as a fluid path, use a suitable thread sealant and tighten accordingly.
- 2. Connect the swivel on the opposite end of the axle as the handle, use suitable thread sealant and tighten accordingly.
 - * See parts list image for orientation of swivel*
- 3. Attach outlet hose to the outlet fitting located in the hub, use a suitable thread sealant and tighten accordingly.
- 4. Attach supply hose to the hose reel swivel, use a suitable thread sealant and tighten accordingly.
- 5. Use 1/2" or 13 mm bolts when securing the hose reel to ceiling or wall.
- 6. The hose reel is ready for operation.

NOTE: THREAD SEALANT NOT INCLUDED

WARNING!

Exposure of skin directly to pressurized air or fluids could result in severe bodily injury!

Warning. Only trained and qualified personnel should install or replace the device.

Warning. De-pressurize prior to servicing.



DHRA50150/300/450

Industrial Hose Reels

AVAILABLE A-FRAME ACCESSORIES



Hose Reel Hose Guide

- DHRA50150/SS use part #2100462
- DHRA50300/SS use part #2100463
- DHRA50450 use part #2100503
- Protects hose when pulling out at an angle
- 4-way pinch-proof stainless steel guides

Hose Reel Stacking Kit

- Part #2100437
- Fits all DHRA hose reels
- Stacks up to 4 hose reels high
- Powder-coated steel construction





Electric Hose Reel Motor Kit

- Part #2103410
- Fits all DHRA hose reels
- Allows for effortless rewinding of hose
- Free spin allows for easy pulling out of hose
- Stainless steel hardware

Hose Reel Cart

- Part #2100465
- Fits all DHRA hose reels
- Easy storage and movement
- Powder-coated steel frame
- Solid polyurethane wheels





12 Volt DC Variable Speed Controller Rewind Kit

- Part #DMC12V
- Fits all DHRA hose reels
- 30 amp auto-reset circuit breaker
- Variable speed knob with built-in on/off function
- Reversible powder-coated mounting plate for left or right orientation
- Sealed housing

