

# **Project Painter Plus**

3A0248D


#### **Patent Pending**

- For portable spray applications of architectural paints and coatings - (Specifications, page 9.)




#### IMPORTANT SAFETY INSTRUCTIONS

Read all warnings and instructions in this manual and on the sprayer cord. Save these instructions. See page 9 for model series information including dispense rate, recommended hose length, guns, and maximum working pressure.



Use water-based or mineral spirit-type materials only. Do not use materials having flash points lower than 70° F (21° C). This includes, but is not limited to, acetone, xylene, toluene, or naptha. For more information about your material, request MSDS from distributor or retailer. retailer.



If you need additional assistance or if you are having problems with the sprayer, contact the **GRACO PRODUCT HELPLINE** at **888-541-9788**.



# **Warnings**

The following warnings are for the setup, use, grounding, maintenance and repair of this equipment. The exclamation point symbol alerts you to a general warning and the hazard symbol refers to procedure-specific risks. Refer back to these warnings. Additional, product-specific warnings may be found throughout the body of this manual where applicable.

#### **Grounding Instructions**


This product must be grounded. In the event of an electrical short circuit, grounding reduces the risk of electric shock by providing an escape wire for the electric current. This product is equipped with a cord having a grounding wire with an appropriate grounding plug. The plug must be plugged into an outlet that is properly installed and grounded in accordance with all local codes and ordinances.

## **M** WARNING



#### **GROUNDING**

- Improper installation of the grounding plug is able to result in a risk of electric shock.
- When repair or replacement of the cord or plug is required, do not connect the grounding wire to either flat blade terminal.
- The wire with insulation having an outer surface that is green with or without yellow stripes is the grounding wire.
- Check with a qualified electrician or serviceman when the grounding instructions are not completely understood, or when in doubt as to whether the product is properly grounded.
- Do not modify the plug provided; if it does not fit the outlet, have the proper outlet installed by a qualified electrician.
- This product is for use on a nominal 120V circuit and has a grounding plug similar to the plug illustrated in the figure below.



- Only connect the product to an outlet having the same configuration as the plug.
- Do not use an adapter with this product.

#### **Extension Cords:**

- Use only a 3-wire extension cord that has a 3-blade grounding plug and a 3-slot receptacle that accepts the plug on the product.
- Make sure your extension cord is not damaged. If an extension cord is necessary, use 12 AWG (2.5 mm²) minimum to carry the current that the product draws.

An undersized cord results in a drop in line voltage and loss of power and overheating.

## **WARNING**



#### FIRE AND EXPLOSION HAZARD

Flammable fumes, such as solvent and paint fumes, in work area can ignite or explode. To help prevent fire and explosion:



- Do not spray flammable or combustible materials near an open flame or sources of ignition such as cigarettes, motors, and electrical equipment. Only use water-based or mineral spirit-type materials with a flash point greater than 70° F (21° C).
- Paint or solvent flowing through the equipment is able to result in static electricity. Static electricity
  creates a risk of fire or explosion in the presence of paint or solvent fumes. All parts of the spray system, including the pump, hose assembly, spray gun, and objects in and around the spray area shall
  be properly grounded to protect against static discharge and sparks. Use conductive or grounded
  high-pressure airless paint sprayer hoses.
- Verify that all containers and collection systems are grounded to prevent static discharge.
- Connect to a grounded outlet and use grounded extensions cords. Do not use a 3-to-2 adapter.
- Do not use a paint or a solvent containing halogenated hydrocarbons.
- Keep spray area well-ventilated. Keep a good supply of fresh air moving through the area. Keep pump assembly in a well ventilated area. Do not spray pump assembly.
- Do not smoke in the spray area.
- Do not operate light switches, engines, or similar spark producing products in the spray area.
- Keep area clean and free of paint or solvent containers, rags, and other flammable materials.
- Know the contents of the paints and solvents being sprayed. Read all Material Safety Data Sheets (MSDS) and container labels provided with the paints and solvents. Follow the paint and solvents manufacturer's safety instructions.
- Fire extinguisher equipment shall be present and working.
- Sprayer generates sparks. When flammable liquid is used in or near the sprayer or for flushing or cleaning, keep sprayer at least 20 feet (6 m) away from explosive vapors.



#### **SKIN INJECTION HAZARD**

- Do not aim the gun at, or spray any person or animal.
- Keep hands and other body parts away from the discharge. For example, do not try to stop leaks with any part of the body.
- Always use the nozzle tip guard. Do not spray without nozzle tip guard in place.
- Use nozzle tips.
  - Use caution when cleaning and changing nozzle tips. In the case where the nozzle tip clogs while spraying, follow the **Pressure Relief Procedure** for turning off the unit and relieving the pressure before removing the nozzle tip to clean.
  - Do not leave the unit energized or under pressure while unattended. When the unit is not in use, turn off the unit and follow the **Pressure Relief Procedure** for turning off the unit.
  - High-pressure spray is able to inject toxins into the body and cause serious bodily injury. In the event that injection occurs, get immediate surgical treatment.
  - Check hoses and parts for signs of damage. Replace any damaged hoses or parts.
  - This system is capable of producing 2800 psi. Use replacement parts or accessories that are rated a minimum of 2800 psi.
  - Always engage the trigger lock when not spraying. Verify the trigger lock is functioning properly.
  - Verify that all connections are secure before operating the unit.
  - Know how to stop the unit and bleed pressure quickly. Be thoroughly familiar with the controls.

## **MARNING**



#### **EQUIPMENT MISUSE HAZARD**

Misuse can cause death or serious injury.

- Always wear appropriate gloves, eye protection, and a respirator or mask when painting.
- Do not operate or spray near children. Keep children away from equipment at all times.
- Do not overreach or stand on an unstable support. Keep effective footing and balance at all times.
- Stay alert and watch what you are doing.
- Do not operate the unit when fatigued or under the influence of drugs or alcohol.
- Do not kink or over-bend the hose.
- Do not expose the hose to temperatures or to pressures in excess of those specified by manufacturer.
- Do not use the hose as a strength member to pull or lift the equipment.



#### **ELECTRIC SHOCK HAZARD**

Improper grounding, setup, or usage of the system can cause electric shock.

- Turn off and disconnect power cord before servicing equipment.
- Use only grounded electrical outlets.
- Use only 3-wire extension cords.
- Ensure ground prongs are intact on sprayer and extension cords.
- Do not expose to rain. Store indoors.



#### PRESSURIZED ALUMINUM PARTS HAZARD

Do not use 1, 1, 1-trichloroethane, methylene chloride, other halogenated hydrocarbon solvents or fluids containing such solvents in pressurized aluminum equipment. Such use can cause serious chemical reaction and equipment rupture, and result in death, serious injury, and property damage.



#### **MOVING PARTS HAZARD**

Moving parts can pinch or amputate fingers and other body parts.

- Keep clear of moving parts.
- Do not operate equipment with protective guards or covers removed.
- Pressurized equipment can start without warning. Before checking, moving, or servicing equipment, follow the Pressure Relief Procedure in this manual. Disconnect power or air supply.



#### TOXIC FLUID OR FUMES HAZARD

Toxic fluids or fumes can cause serious injury or death if splashed in the eyes or on skin, inhaled, or swallowed.

- Read MSDS's to know the specific hazards of the fluids you are using.
- Store hazardous fluid in approved containers, and dispose of it according to applicable guidelines.



#### PERSONAL PROTECTIVE EQUIPMENT

You must wear appropriate protective equipment when operating, servicing, or when in the operating area of the equipment to help protect you from serious injury, including eye injury, inhalation of toxic fumes, burns, and hearing loss. This equipment includes but is not limited to:

- Protective eye wear
- Clothing and respirator as recommended by the fluid and solvent manufacturer
- Gloves
- Hearing protection

#### **CALIFORNIA PROPOSITION 65**

This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm. Wash hands after handling.


## **MARNING**

#### **SETUP**




Remove spray tip and guard from gun.

2




Connect hose to gun and sprayer.

3



Turn Power Switch OFF. Plug sprayer into grounded outlet.

#### **FLUSHING**



ti14953a

Turn Pressure Control Knob left (counterclockwise) to minimum pressure.

2

Lift Spray/Prime valve to PRIME.

3



Unclip small drain tube from large suction tube and place into waste pail.


4



If spraying oil-based materials,\* submerge suction tube in paint thinner or compatible oil-based cleaning solution.

If spraying water-based materials, submerge suction tube in water.

5




ti13961a

Turn Power switch ON. With Spray/Prime valve still at PRIME, turn Pressure Control Knob to right (clockwise) until pump starts.

6




5




#### **PRIMING**

1



Submerge suction tube in paint. Turn power switch ON, and trigger gun into waste pail. When paint comes out of drain tube, lower prime/spray valve to SPRAY.

2



When paint comes out of gun, release trigger. Pump will build up pressure, and motor will stop.

3



Transfer drain tube to paint pail.

#### **SPRAYING**

1



Put trigger safety lever in SAFETY ON position.

2



Install tip and guard on gun, and hand tighten. Your are now ready to spray.

3




If tip clog occurs, this spray tip reverses, enabling you to quickly clear obstructions without disassembly.

4



Turn Pressure Control Knob right (clockwise) to increase pressure at the gun, and turn it left (counterclockwise) to decrease the pressure.

5




GOOD PATTERN

Point Gun at surface to be sprayed about 12 in. (304 mm) away from surface, and begin moving the gun before you trigger it. A good spray pattern is evenly distributed as it hits the surface. Set the pressure so it is just high enough to spray without "tails". If tails persist at the highest pressure, a smaller tip is needed to spray the material or material may need to be thinned.

## **MARNING**


## SHUTDOWN AND CLEANING - WATER-BASED PAINTS\*

1




Turn power switch OFF. Place suction tube and drain tube into empty waste pail. Lift spray/prime valve to PRIME to relieve fluid pressure.

2



With the trigger safety ON, remove tip and guard from gun and place into waste pail for further cleaning.


3



Thread power flush attachment onto garden hose. Rinse paint off of suction tube, drain tube and inlet screen.


ti14959a

4




Unscrew inlet screen from suction tube. Thread power flush attachment onto suction tube.

5




Trigger gun into paint pail and lower spray/prime valve to SPRAY. Turn power switch ON to push paint in hose into paint pail. When water comes out of the gun, keep gun triggered and move aim of gun into waste pail.

6



Trigger gun into waste pail for 1-2 minutes until relatively clear water comes out of gun.

7




Lift prime/spray valve to PRIME. Let water flow through the sprayer and into waste pail for 20 seconds.


#### **SHUTDOWN AND CLEANING - WATER-BASED PAINTS\***

9

8




Turn power switch OFF. Remove power flush attachment from suction tube.




Clean tip, guard and inlet screen with a brush. Remove filter from spray gun, and clean with a brush. Reassemble spray gun guard/tip and filter.

10




Submerge suction tube and drain tube in storage fluid. Always use Graco pump armor or mineral spirits/paint thinner for storage fluid. Lift spray/prime valve to PRIME. Turn power switch ON.




Turn pressure control knob to right (clockwise) until pump starts.

12



When storage fluid comes out of drain tube, turn power switch OFF.



Lower prime/spray valve to SPRAY.

14

Install inlet screen on suction tube for storage.

# **Specifications**

This equipment is not intended for use with flammable or combustible materials used in places such as cabinet shops or other "factory", or fixed locations. If you intend to use this equipment in this type of application, you must comply with NFPA 33 and OSHA requirements for the use of flammable and combustible materials.

Model Name	Series	Dispense Rate gpm	Hose Length Maximum		Gun Model	Maximum Working Pressure		
		(lpm)	una Diameter	Tiose Length	Model	PSI	MPa	bar
Project Painter Plus	А	0.24 gpm (0.91 lpm)	1/4 in. x 25 ft (6.4 mm x 7.5 m)	50 ft (15 m)	SG2	2800	19	193


## Installation

# **Grounding and Electric Requirements**











**Sprayer** must be grounded. Grounding reduces the risk of static and electric shock by providing an escape wire for electrical current due to static build up or in the event of a short circuit.

- The 120 Vac sprayers require a 120 Vac, 60 Hz, 15A circuit with a grounding receptacle.
- Never use an outlet that is not grounded or an adapter.



 Do not use the sprayer if the electrical cord has a damaged ground prong.



Recommended extension cords for use with this sprayer:

- 50 ft (15.0 m) 14 AWG (2.1 mm<sup>2</sup>)
- 100 ft (30.0 m) 12 AWG (3.3 mm<sup>2</sup>)

**Spray gun:** ground through connection to a properly grounded fluid hose and pump.

**NOTE:** Smaller gauge or longer extension cords may reduce sprayer performance.

Fluid supply container: follow local code.

Solvent pails used when flushing: follow local code. Use only conductive metal pails, placed on a grounded surface such as concrete. Do not place the pail on a nonconductive surface, such as paper or cardboard, which interrupts grounding continuity.

<u>Grounding the metal pail</u>: connect a ground wire to the pail by clamping one end to pail and other end to ground such as a water pipe.

Maintaining grounding continuity when flushing or relieving pressure: hold metal part of the spray gun firmly to the side of a grounded metal pail, then trigger the gun.



#### **Thermal Overload**

Motor has a thermal overload switch to shut itself down if overheated. If unit overheats, allow approximately 45 minutes for unit to cool. Once cool, switch will close and unit will restart.



ti5572a


To reduce risk of injury from motor starting unexpectedly when it cools, always turn power switch OFF if motor shuts down.

# **Notes**

# **Component Identification - Project Painter Plus**

Α	Airless spray gun	Dispenses fluid.
В	Power switch	Turns sprayer ON and OFF.
С	Pressure control knob	Increases (clockwise) and decreases (counter-clockwise) fluid pressure in pump, hose, and spray gun.
C1	Setting Indicator	To select function, align symbol on pressure control knob with setting indicator, page 14.
D	Pump fluid outlet fitting	Threaded connection for paint hose.
G	Suction tube	Draws fluid from paint pail into pump.
Н	Prime tube (with diffuser)	Drains fluid in system during priming and pressure relief.
J	Prime/Spray valve	<ul> <li>In PRIME position directs fluid to prime tube.</li> <li>In SPRAY position directs pressurized fluid to paint hose.</li> <li>Automatically relieves system pressure in overpressure situations.</li> </ul>
L	Inlet screen	Prevents debris from entering pump.
М	Paint hose	Transports high-pressure fluid from pump to spray gun.
N	Handle	Used to help transport sprayer.
Q	Tip guard	Reduces risk of fluid injection injury.
R	Reversible spray tip	<ul> <li>Atomizes fluid being sprayed, forms spray pattern and controls fluid flow according to hole size.</li> <li>Reverse unclogs plugged tips without disassembly.</li> </ul>
S	Gun trigger safety lever (page 14)	Prevents accidental triggering of spray gun.
Т	Gun fluid inlet fitting	Threaded connection for paint hose.
U	Power Flush attachment	Connects garden hose to suction tube for power flushing water-base fluids.
V	Gun fluid filter	Filters fluid entering spray gun to reduce tip clogs.
W	Pail Hook	Holds material pail.
Х	Power Cord	Supplies Project Painter Plus with electricity.

## **Project Painter Plus**



## **Operation**



## **Trigger Lock**

Always engage the trigger lock when you stop spraying to prevent the gun from being triggered accidentally by hand or if dropped or bumped.





Trigger Locked

**Trigger Unlocked** 

#### **Pressure Relief Procedure**

Follow this Pressure Relief Procedure whenever you stop spraying and before cleaning, checking, servicing, or transporting equipment.










1. Turn power switch OFF and unplug power cord.




Lift prime/spray valve to PRIME to relieve pressure.



3. Hold gun firmly to side of pail. Trigger the gun to relieve pressure.




4. Engage trigger lock.



NOTE: Leave prime/spray valve in the PRIME position until you are ready to spray again.

If you suspect the spray tip or hose is clogged or that pressure has not been fully relieved after following the steps above, VERY SLOWLY loosen tip guard retaining nut or hose end coupling to relieve pressure gradually, then loosen completely. Clear hose or tip obstruction. Read Unclogging Spray Tip, page 18.


## **Pressure Control Knob Settings**




NOTE: To select function, align symbol on pressure control knob with setting indicator on sprayer.

# **Setup**


1. Unscrew tip and guard assembly from gun.



2. Uncoil hose and connect one end to gun. Use two wrenches to tighten securely.



3. Connect other end of hose to sprayer.




**NOTE:** If hose is already connected, make sure connections are tight.

4. Turn OFF power switch.



5. Turn Pressure Control Knob all the way left (counter-clockwise) to minimum pressure.




## Prime and Flush Storage Fluid

**NOTE:** These units are not intended for lacquers.

Before you use your sprayer for the first time or begin a new spraying project, you need to prime the sprayer and flush the storage fluid out of the sprayer.

#### Oil- or Water-based Materials


- When spraying water-based materials, flush the system thoroughly with water.
- When spraying oil-based materials, flush the system thoroughly with mineral spirits or compatible, oil-based flushing solvent.
- To spray water-based materials after spraying oil-based materials, flush the system thoroughly with water first. The water flowing out of prime tube should be clear and solvent-free before you begin spraying the water-based material.
- To spray oil-based materials after spraying water-based materials, flush the system thoroughly with mineral spirits or a compatible oil-based flushing solvent first. The solvent flowing out of the prime tube should not contain any water.
- When flushing with solvents, ground pail and gun. Read Grounding and Electric Requirements, page 10.
- To avoid fluid splashing back on your skin or into your eyes, always aim gun at inside wall of pail.



1. Make sure the power switch is OFF and the sprayer is unplugged.



2. Separate prime tube (smaller) from suction tube (larger).



3. Place prime tube in waste pail.




ti14962a

4. Submerge suction tube in water or flushing solvent.



5. Lift prime/spray valve to PRIME.



- Plug sprayer in a grounded outlet.
- Turn power switch ON.



8. Align setting indicator with prime/clean setting on pressure control knob until pump starts, page 14.



ti12948a

- 9. When sprayer starts pumping, flushing solvent and air bubbles will be purged from system. Allow fluid to flow out of prime tube, into waste pail, for 30 to 60 seconds.
- 10. Turn power switch OFF.

11. Transfer suction tube to paint pail and submerge suction tube in paint.




ti14963a


12. Turn power switch ON.



- 13. When you see paint coming out of prime tube:
  - a. Point gun into waste pail.
  - b. Unlock gun trigger lock.



- c. Pull and hold gun trigger.
- d. Lower Prime/Spray valve to SPRAY.



- 14. Continue to trigger gun into waste pail until you see only paint coming out of gun.
- 15. Release trigger. Engage trigger lock.




16. Transfer prime tube to paint pail and clip prime tube to suction tube.




- Motor stopping indicates pump and hose are primed with paint.
- If motor continues to run the sprayer is not properly primed. To reprime repeat step 8.


## **Install Tip and Guard on Gun**




Engage trigger lock.



2. Verify tip and guard parts are assembled in order shown.






ti12966a



## **Spraying Techniques**

#### **Preventing Excessive Tip Wear**

- Spray should be atomized (evenly distributed, no gaps at edges). Start at low pressure setting, increase pressure a little at a time until you see a good spray pattern, without tails.
- Spray at lowest pressure that atomizes paint.
- If maximum sprayer pressure is not enough for a good spray pattern, tip is too worn. See Reversible Spray Tip Selection Chart, page 19.



**NOTE:** If tails persist when spraying at the highest pressure, a smaller tip is needed or the material may need to be thinned.

#### **Adjust Spray Pressure**

This sprayer is set up for most airless spraying applications. Details on tip selection, tip wear, coat thickness, etc. are provided on page 19.



**NOTE:** Motor only runs when gun is triggered. Sprayer is designed to stop pumping when gun trigger is released.

Align setting indicator with function symbol on Pressure Control knob, page 14.

- Turning knob to right (clockwise), increases pressure at gun.
- Turning it left (counter-clockwise), decreases pressure.
- General spraying instructions are provided in Getting Started with Basic Spraying Techniques section of this manual, page 20.

## **Unclogging Spray Tip**



To avoid fluid splashback:


- Never pull gun trigger when arrow-shaped handle is between SPRAY and UNCLOG positions.
- Tip must be pushed all the way into guard.
- 1. To unclog tip obstruction, engage trigger lock.



2. Point arrow-shaped handle backward to unclog position.



- 3. Aim gun at piece of scrap or cardboard.
- 4. Unlock trigger lock. Pull trigger to clear clog.



5. When obstruction is cleared, engage trigger lock and rotate arrow-shaped handle back to SPRAY position.



Point the arrow-shaped handle on the spray tip forward to SPRAY and backward to UNCLOG obstructions.

## **Tip Selection**

#### **Selecting Tip Hole Size**

Tips come in a variety of hole sizes for spraying a range of fluids. Your sprayer includes an 0.015 in (0.38 mm) tip for use in most spraying applications. Use the following table to determine the range of recommended tip hole sizes for each fluid type. If you need a tip other than the one supplied, see the **Tip Selection Chart** below.

#### HINTS:

- As you spray, the tip wears and enlarges. Starting with a tip hole size smaller than the maximum will allow you to spray within the rated flow capacity of the sprayer.
- Maximum tip hole sizes supported by the sprayer:
  - Project Painter Plus Models: 0.015 in. (0.38 mm)

	Coatings				
Tip Hole Size	Stains	Enamels	Primers	Interior Paints	Exterior Paints
0.011 in. (0.28 mm)	~				
0.013 in. (0.33 mm)	~	~	~	~	
0.015 in. (0.38 mm)		~	~	~	V
0.017 in. (0.43 mm)			~	V	<b>V</b>

## **Choosing the Correct Tip**

Consider coating and surface to be sprayed. Make sure you use best tip hole size for that coating and best fan width for that surface.

#### Tip Hole Size

Tip hole size controls flow rate - the amount of paint that comes out of the gun.

#### HINTS:

- Use larger tip hole sizes with thicker coatings and smaller tip hole sizes with thinner coatings.
- Tips wear with use and need periodic replacement.

#### **Understanding Tip Number**


The last three digits of tip number (i.e.: 286413) contain information about hole size and fan width on surface when gun is held 12 in. (30.5 cm) from surface being sprayed.

#### Fan Width

Fan width is the size of the spray pattern, which determines the area covered with each stroke. Narrower fans deliver a thicker coat, and wider fans deliver a thinner coat.

#### HINTS:

- Select a fan width best suited to the surface being sprayed.
- Wider fans allow provide better coverage on broad, open surfaces.
- Narrower fans provide better control on small, confined surfaces.




Last two digits = tip hole size in thousands of an inch


## **Getting Started With Basic Techniques**

Use a piece of scrap cardboard to practice these basic spraying techniques before you begin spraying the surface.

 Hold gun 12 in. (30 cm) from surface and aim straight at surface. Tilting gun to direct spray angle causes an uneven finish.




 Flex wrist to keep gun pointed straight. Fanning gun to direct spray at angle causes uneven finish.




## **Triggering Gun**

Pull trigger after starting stroke. Release trigger before end of stroke. Gun must be moving when trigger is pulled and released.



## **Aiming Gun**

Aim tip of gun at bottom edge of previous stroke, overlapping each stroke by half.




# **Shutdown and Cleaning**

## **Pail Flushing**

- For short term shutdown periods (overnight to two days) refer to Short Term Storage, page 25.
- For flushing after spraying oil-based coatings, use compatible oil-based flushing fluid or mineral spirits.
   Read Priming and Flushing Storage Fluid, page 16.
- For flushing after spraying water-based coatings, use water. Read Priming and Flushing Storage Fluid, page 16 or Power Flush, page 23.



- 1. Relieve pressure, page 14.
- 2. Remove tip and guard assembly from gun and place in flushing fluid.
- 3. Lift suction tube and prime tube from paint pail. Let them drain into paint pail for a while.
- 4. Separate prime tube (smaller) from suction tube (larger).




5. Place empty waste and water or solvent pails side by side.



6. Place prime tube in waste pail.




7. Submerge suction tube in water or flushing solvent.



Turn pressure control knob to the Prime/Clean setting.



9. Turn power switch ON.




- 10. Flush until approximately 1/3 of the flushing fluid is emptied from the pail.
- 11. Turn power switch OFF.




**NOTE:** Step 12 is for returning paint in hose back to paint pail. One 50-ft hose holds approximately 1-quart (1-liter) of paint.

- 12. To preserve paint in hose:
  - a. Point gun into paint pail.
  - b. Unlock gun trigger lock.




- c. Pull and hold gun trigger.
- d. Lower prime/spray valve to SPRAY.




e. Turn power switch ON.




f. Continue to hold gun trigger until you see paint diluted with flushing fluid starting to come out of gun. 13. While continuing to trigger gun, quickly move gun to redirect spray into waste pail. Continue triggering gun into waste pail until flushing fluid dispensed from gun is relatively clear.



14. Stop triggering gun. Engage the trigger lock.



15. Lift prime/spray valve to PRIME.



16. Turn power switch OFF.



- 17. Clean InstaClean Fluid Filter and gun, page 24.
- 18. Fill unit with Pump Armor<sup>™</sup> storage fluid. Read Long Term Storage, page 25.

#### **Power Flush**


Power flushing is a faster method of flushing. It can only be used after spraying water-based coatings.



- 1. Relieve pressure, page 14.
- 2. Remove tip and guard assembly from gun and place in waste pail.
- 3. Place empty waste and paint pails side by side.




- 4. Lift suction tube and prime tube from paint pail. Let them drain into paint for a while.
- 5. Place suction and prime tube in waste pail.
- 6. Turn Pressure Control knob to the Prime/Clean setting.




- 7. Screw power flush attachment to garden hose. Close valve.
- 8. Turn on water. Open valve. Rinse paint off suction tube, prime tube and inlet screen.




9. Turn lever to close power flush attachment.



10. Unscrew inlet screen from suction tube. Place inlet screen in waste pail.



11. Connect garden hose to suction tube with Power Flush attachment. Leave prime tube in waste pail.



12. Turn power switch ON.



13. Open lever on Power Flush attachment.




- 14. Circulate water through sprayer, into waste pail, for 20 seconds.
- 15. Turn power switch OFF.




**NOTE:** Step 16 is for returning paint in hose back to paint pail. One 50-ft (15-m) hose holds approximately 1-quart (1-liter) of paint.

- 16. To preserve paint in hose:
  - a. Point gun into paint pail.
  - b. Unlock gun trigger lock.



- c. Pull and hold gun trigger.
- d. Lower prime/spray valve to SPRAY.




e. Turn power switch ON.




- f. Continue to hold gun trigger until you see paint diluted with water starting to come out of gun.
- 17. While continuing to trigger gun, quickly move gun to redirect spray into waste pail. Continue triggering gun into waste pail until water coming out of gun is relatively clear.



18. Stop triggering gun. Engage trigger lock.




19. Lift prime/spray valve to PRIME.




20. Turn power switch OFF.



21. Turn off garden hose. Close Power Flush attachment.



22. Unscrew Power Flush attachment from suction tube.



- 23. Clean InstaClean fluid filter and gun, page 24.
- 24. Fill unit with Pump Armor<sup>™</sup> storage fluid. Read Long Term Storage, page 25.

## **Cleaning Gun**

- Clean gun fluid filter (d)
  with water or flushing solvent and a brush every
  time you flush the system.
  Replace gun filter if damaged.
- Remove tip and guard and clean with water or flushing solvent. A soft brush can be used to loosen and remove dried on material if needed.
- Wipe paint off outside of gun using a soft cloth moistened with water or flushing solvent.



# **Storage**

## **Short Term Storage**

(up to 2 days)









- 1. Relieve pressure, page 14.
- 2. Leave suction tube and prime tube in paint pail.



ti14964a


3. Cover paint pail and hoses tightly with plastic wrap.



ti14965a

Engage trigger lock.

4.




- b. Leave gun attached to hose.
- c. If you have not already cleaned them, remove tip and guard from gun and clean with water or flushing solvent. A soft brush can be used to loosen and remove dried on material if needed.




d. Wipe paint off outside of gun using a soft cloth moistened with water or flushing solvent.

## **Long Term Storage**


(more than 2 days)



- Always circulate Pump Armor storage fluid through system after cleaning. Water left in sprayer will corrode and damage pump.
- Follow Shutdown and Cleaning, page 21, or Power Flush Cleaning, page 23.
- 1. Place suction tube in Pump Armor storage fluid bottle and prime tube in waste pail.




2. Lift prime/spray valve to PRIME.



3. Turn power switch ON.




4. Turn pressure control knob clockwise until the pump turns on.



5. When storage fluid comes out of prime tube (5-10 seconds) turn power switch OFF.



6. Lower prime/spray valve to SPRAY to keep storage fluid in sprayer during storage.




# **Stowing Sprayer**


#### **NOTICE**

- To prevent damage to the equipment, make sure all water is drained out of sprayer and hoses before storing.
- Do not allow water to freeze in sprayer or hose.
- Do not store sprayer under pressure.


1. Screw inlet screen onto suction tube.



2. Coil hose. Leave it connected to sprayer. Wrap hose around hose wrap bracket.



- 3. Secure a plastic bag around suction tube to catch any drips.
- 4. Store sprayer indoors.



## **Maintenance and Service\***

#### **NOTICE**


**Protect the internal drive parts of this sprayer from water.** Openings in shroud allow cooling of mechanical parts and electronics inside. If water gets into these openings, the sprayer could malfunction or be permanently damaged.

## **Caring for Sprayer**

Keep sprayer and all accessories clean and in good working order.



To avoid overheating motor, keep vent holes in shroud clear for air flow. Do not cover sprayer while spraying.



ti14967a

#### **Paint Hoses**

Check hose for damage every time you spray. Do not attempt to repair hose if hose jacket or fittings are damaged. Do not use hoses shorter than 25 ft (7.6 m). Use two wrenches to tighten.

## **Tips**

 Always clean tips with compatible solvent and brush after spraying.



- Tips may require replacement after 15 gallons (57 liters) or they may last through 60 gallons (227 liters) depending on abrasiveness of paint.
- Do not spray with worn tip.

\* Please refer to the Part List (page 32) for a list of replaceable parts.

# **Troubleshooting**



Check everything in this Troubleshooting Table before you bring the sprayer to an authorized service center.

Problem	Cause	Solution
Power switch is on and sprayer is plugged in, but motor does not run,	Pressure is set at zero pressure.	Turn pressure control knob clock- wise to increase pressure setting.
and pump does not cycle.	Motor or control is damaged.	Take sprayer to an authorized service center.*
	Electric outlet is not providing power.	Try a different outlet or plug in something that you know is work- ing to test outlet.
		Reset building circuit breaker or replace fuse.
	Extension cord is damaged.	Replace extension cord. Read Grounding and Electric Require- ments, page 10.
	Sprayer electric cord is damaged.	Check for broken insulation or wires. Replace electric cord if damaged.
	Paint and/or water is frozen or hard- ened in pump.	Unplug sprayer from outlet. If frozen do NOT try to start sprayer until it is completely thawed or you may damage the motor, control board and/or drivetrain.
		Make sure power switch is OFF. Place sprayer in a warm area for several hours. Then plug in powercord and turn sprayer ON. Slowly increase pressure setting to see if motor will start.
		If paint is hardened in sprayer, pump packings, valves, drivetrain or pressure switch may need to be replaced. Take sprayer to an authorized service center.*

<sup>\*</sup> Please refer to the **Part List** (page 32) for a list of replaceable parts.

Problem	Cause	Solution
Pump does not prime.	Inlet valve check ball is stuck.	Remove suction tube and place a pencil into the inlet section to dislodge the ball, allowing pump to prime properly. OR Power Flush sprayer (see Operation manual).
	Inlet valve check ball or seat is dirty.	Remove inlet housing. Clean or replace ball and seat.
	Outlet valve check ball is stuck.	Unscrew outlet valve with a 3/4 in. socket. Remove and clean assembly.
	Suction tube is not immersed	Make sure suction tube is immersed in paint.
	Suction tube is leaking.	Tighten suction tube connection. Inspect for cracks or vacuum leaks.
	Pump does not prime with fluid.	Remove suction tube from paint. Prime pump with water or solvent-based flushing fluid.
Pump cycles but does not build up	Pump is not primed.	Prime pump.
pressure.	Inlet screen is clogged.	Clean debris off inlet screen and make sure suction tube is immersed in fluid.
	Suction tube is not immersed in paint.	Make sure suction tube is immersed in paint.
	Paint pail is empty.	Refill hopper or paint pail. Reprime sprayer.
	Suction tube is leaking.	Inlet tube fitting improperly or not securely attached.
	Prime/Spray Valve is worn or obstructed with debris.	Take sprayer to authorized service center.*
	Pump check ball is stuck.	Read <i>Pump does not prime</i> section above.
Pump cycles, but paint only dribbles or spurts when spray gun is triggered.	Pressure is set too low.	Turn Pressure Control Knob clockwise to increase pressure setting which will turn on motor to build pressure.
	Spray tip is clogged.	Unclog spray tip.
	Spray gun fluid filter is clogged.	Clean or replace gun fluid filter.
	Spray tip is too large or worn.	Replace spray tip.


Problem	Cause	Solution	
Pressure is set at maximum but cannot achieve a good spray pattern.	Reversible spray tip is in UNCLOG position.	Rotate arrow-shaped handle on spray tip so it points forward in SPRAY position.	
	Spray tip is too large for sprayer.	Select smaller spray tip.	
	Spray tip is worn beyond capability of sprayer.	Replace spray tip.	
	Extension cord is too long or not heavy enough gauge.	Replace extension cord. <b>Grounding</b> and Electrical Requirements, page 10.	
	Spray gun fluid filter is clogged.	Clean or replace spray gun fluid filter.	
	Inlet screen is clogged.	Clean debris off inlet screen.	
	Pump valves are worn.	Check for worn pump valves.	
		a. Prime sprayer with paint	
		b. Trigger gun momentarily. When trigger is released, pump should cycle momen- tarily and stop. If pump con- tinues to cycle, pump valves may be worn. Take sprayer to authorized service center.*	
	Material too thick.	Thin material.	
	Hose too long (if extra section is added).	Remove section of hose.	
Spray gun stopped spraying.	Pump was not primed with flushing fluid.	Remove suction tube from paint. Prime pump with water or flushing solvent-based flushing fluid.	
	Suction tube is leaking.	Tighten suction tube connection. Inspect for cracks or vacuum leaks.	
	Prime/Spray Valve is plugged.	Clean/replace prime tube as necessary. Take sprayer to authorized service center if valve is plugged.*	
	Spray tip is clogged.	Unclog spray tip.	
When paint is sprayed, it runs down	Coat is going on too thick.	Move gun faster.	
the wall or sags.		Choose a tip with smaller hole size.	
		Choose tip with wider fan.	
		Make sure gun is far enough from surface.	
When paint is sprayed, coverage is	Paint coating is going on too thin.	Move gun slower.	
inadequate.		Choose tip with larger hole size.	
		Choose tip with narrower fan.	
		Make sure gun is close enough to surface.	

Problem	Cause	Solution
Fan pattern varies dramatically while spraying.  OR	Pressure control switch is worn and causing excessive pressure variation.	Take sprayer to authorized service center.*
Sprayer does not turn on promptly when resuming spraying.		
Cannot trigger spray gun.	Spray gun trigger lock is locked.	Rotate trigger safety lever to unlock trigger lock, page 14.
Paint is coming out of pressure control switch.	Pressure control switch is worn.	Take sprayer to authorized service center.*
Prime/Spray valve actuates automatically relieving pressure through prime tube.	System is over pressurizing.	Take sprayer to authorized service center.*
Paint leaks down outside of pump.	Pump packings are worn.	Replace sprayer.
Motor is hot and runs intermittently.  Motor automatically shuts off due to excessive heat. Damage can occur if	Vent holes in enclosure are plugged or sprayer is covered.	Keep vent holes clear of obstructions and overspray and keep sprayer open to air.
cause is not corrected.  Thermal Overload, page 10.	Extension cord is too long or not a heavy enough gauge.	Replace extension cord. Read  Grounding and Electrical  Requirements, page 10.
	Unregulated electrical generator being used has excessive voltage.	Use electrical generator with a proper voltage regulator. Sprayer requires 120VAC, 60 Hz, 1500-Watt generator.
	Sprayer was operated at high pressure with very small tip which causes frequent motor starts and excessive heat build up.	Decrease pressure setting or increase tip size.
Building circuit breaker opens after sprayer operates for 5 to 10 minutes.	Too many appliances are plugged in on same circuit.	Free up circuit (unplug things), or use a less busy circuit.
	Sprayer electrical cord is damaged.	Check broken insulation or wires. Replace electrical cord if damaged.
	Extension cord is damaged or too long or not a heavy enough gauge.	Plug in something that you know is working to test extension cord.
		Replace extension cord.

<sup>\*</sup> Please refer to the **Part List** (page 32) for a list of replaceable parts.

# **Parts List**

# **Project Painter Plus Model (257025)**



Ref.	Part	Description	Qty.
1	197607	KIT, suction tube	1
2	243011	GUN, SG2	1
3	24D616	KIT, enclosure and stand	1
4	244035	DEFLECTOR, barbed	1
5	257002	STRAINER	1
6	24D626	SPRAYER (no hose or gun)	1
7	24D617	KIT, front cover	1
8	247339	HOSE 1/4 in x 25 ft	1

## **Technical Data**

	Project Painter Plus
Working pressure range	0-2800 psi (0-19 MPa, 0-193 bar)
Electric motor	7.0A (open frame, universal)
Operating horsepower	3/8
Maximum delivery (with tip)	0.24 gpm (0.91 lpm)
Paint hose	1/4 in. x 25 ft (6.4 mm x 7.5 m)
Maximum tip hole size	0.015 in. (0.38 mm)
Weight, sprayer only	10 lb (4.5 kg)
Weight, sprayer, hose & gun	13.2 lb (5.9 kg)
Dimensions:	
Length	13.8 in. (35.2 cm)
Width	12.1 in. (30.7 cm)
Height	13.8 in. (35.1 cm)
Power cord	18 AWG, 3-wire, 6 ft (1.8 m)
Fluid inlet fitting	3/4 in. internal thread (standard garden hose thread)
Fluid outlet fitting	1/4 NPSM external thread
Inlet screen (on suction tube)	35 mesh (450 micron)
Wetted parts, pump & hose	stainless steel, brass, leather, ultra-high molecular weight polyethylene (UHMWPE), carbide, nylon, aluminum, PVC, polypropylene, fluroelastomer
Wetted parts, gun	aluminum, brass, carbide, nylon, plated steel, stainless steel, UHMWPE, zinc
Generator requirement	1500 Watt minimum
Electrical power requirement	120 Vac, 60 Hz, 15A, 1 phase
Storage temperature range ◆◆	-30° to 160°F (-35° to 71°C)
Operating temperature range 🗸	40° to 115°F (4° to 46°C)

- ♦ When pump is stored with non-freezing fluid. Pump damage will occur if water or latex paint freezes in pump.
- ❖ Damage to plastic parts may result if impact occurs in low temperature conditions.
- ✔ Changes in paint viscosity at very low or very high temperatures can affect sprayer performance.

# **Notes**

# **Notes**

## **Standard Warranty**

Graco warrants all equipment referenced in this document which is manufactured by Graco and bearing its name to be free from defects in material and workmanship on the date of sale to the original purchaser for use. With the exception of any special, extended, or limited warranty published by Graco, Graco will, for a period of twelve months from the date of sale, repair or replace any part of the equipment determined by Graco to be defective. This warranty applies only when the equipment is installed, operated and maintained in accordance with Graco's written recommendations.

This warranty does not cover, and Graco shall not be liable for general wear and tear, or any malfunction, damage or wear caused by faulty installation, misapplication, abrasion, corrosion, inadequate or improper maintenance, negligence, accident, tampering, or substitution of non-Graco component parts. Nor shall Graco be liable for malfunction, damage or wear caused by the incompatibility of Graco equipment with structures, accessories, equipment or materials not supplied by Graco, or the improper design, manufacture, installation, operation or maintenance of structures, accessories, equipment or materials not supplied by Graco.

This warranty is conditioned upon the prepaid return of the equipment claimed to be defective to an authorized Graco distributor for verification of the claimed defect. If the claimed defect is verified, Graco will repair or replace free of charge any defective parts. The equipment will be returned to the original purchaser transportation prepaid. If inspection of the equipment does not disclose any defect in material or workmanship, repairs will be made at a reasonable charge, which charges may include the costs of parts, labor, and transportation.

THIS WARRANTY IS EXCLUSIVE, AND IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.

Graco's sole obligation and buyer's sole remedy for any breach of warranty shall be as set forth above. The buyer agrees that no other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available. Any action for breach of warranty must be brought within two (2) years of the date of sale.

GRACO MAKES NO WARRANTY, AND DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, IN CONNECTION WITH ACCESSORIES, EQUIPMENT, MATERIALS OR COMPONENTS SOLD BUT NOT MANUFACTURED BY GRACO. These items sold, but not manufactured by Graco (such as electric motors, switches, hose, etc.), are subject to the warranty, if any, of their manufacturer. Graco will provide purchaser with reasonable assistance in making any claim for breach of these warranties.

In no event will Graco be liable for indirect, incidental, special or consequential damages resulting from Graco supplying equipment hereunder, or the furnishing, performance, or use of any products or other goods sold hereto, whether due to a breach of contract, breach of warranty, the negligence of Graco, or otherwise.

#### **FOR GRACO CANADA CUSTOMERS**

The Parties acknowledge that they have required that the present document, as well as all documents, notices and legal proceedings entered into, given or instituted pursuant hereto or relating directly or indirectly hereto, be drawn up in English.

Les parties reconnaissent avoir convenu que la rédaction du présente document sera en Anglais, ainsi que tous documents, avis et procédures judiciaires exécutés, donnés ou intentés, à la suite de ou en rapport, directement ou indirectement, avec les procédures concernées.

For the latest information about Graco products, visit www.graco.com.

TO PLACE AN ORDER, contact your Graco distributor or call 1-800-690-2894 to identify the nearest distributor.

All written and visual data contained in this document reflects the latest product information available at the time of publication.

Graco reserves the right to make changes at any time without notice.

For patent information, see www.graco.com/patents.

Original instructions. This manual contains English. MM 3A0248

Graco Headquarters: Minneapolis International Offices: Belgium, China, Japan, Korea

GRACO INC. AND SUBSIDIARIES • P.O. BOX 1441 • MINNEAPOLIS MN 55440-1441 • USA Copyright 2009, Graco Inc. All Graco manufacturing locations are registered to ISO 9001.

www.graco.com Revised October 2013