

#1 in North America for High-Pressure Cleaning Equipment

and 790SS Hot Water Pressure Washers

Electric / Belt Drive

Pressure relief valve protects the machine and user from thermal expansion



with diesel fuel, kerosene or home-heating oil
Control panel includes adjustable temperature

control plus heavy-duty heater and pump motor

manual reset

5 HP, 230V, 1PH Baldor electric motor (Model 795SS) comes with thermal overload protection and

Upright, oil fired burner delivers high efficiency

switches

High quality float valve helps maintain constant pressure and flow and traps sediment or debris. It is recessed at center of chassis for protection and balance

Ground Fault Circuit Interrupter (GFCI breaker) provides additional protection against shock hazard

Hotsy-designed Triplex pumps carry a 7-year limited warranty



Pneumatic tires with inner tubes provide easy maneuverability over pavement or rough terrain

FEATURES

- 2.8 or 3.5 GPM @ 2000 or 3000 PSI
- Oil Fired Burners
- 208V or 230V, 1PH
- 4 to 8.2 HP
- 1330 or 1490 RPM Belt Drive Pumps

Belt tension adjusts easily

Variable upstream detergent injection ensures high-pressure sudsing



Built-in wand and **nozzle holders** provide convenient storage

by turning a single bolt

Model 895SS 3.5 GPM @3000 PSI





Rugged belt drive provides smooth, quiet operation and outstanding reliability

Rust-proof cross linked polyethylene fuel tank eliminates condensation that can contaminate fuel. Fuel gauge in cap.

Model 795SS 3.5 GPM @2000 PSI

Convenient hose-reel bracket accepts swivel or stationary reels

www.Hotsy.com

Nothing Cleans Like a Hotsy!

Oil Fired Burners

2.8 or 3.5 GPM @ 2000 or 3000 PSI

Hotsy 7-Year Pump Warranty

Designed for tough, industrial cleaning.

SPECIFICATIONS												BELT DRIVE	
MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	PUMP MODEL	PUMP RPM	BTU/HR	PORTABILITY	HOSE	SHIP WT
790SS	2.8	2000	4TEFC*	1725	230/1	20	Oil	HHC340R.1	1330	289,900	Std	50′	460
795SS	3.5	2000	5	3450	230/1	24	Oil	HHC340R.1	1490	289,900	Std	50′	460
795SS-208	3.5	2000	5	3450	208/1	27	Oil	HHC340R.1	1490	289,900	Std	50′	500
895SS	3.5	3000	8.2	3450	230/1	36	Oil	HHC506R.1	1490	289,900	Std	50′	480

Dimensions: 37" / x 28"w x 45.5"h

*Totally enclosed fan cooled (TEFC)




Clean better with Hotsy detergents

Hotsy pressure washers and parts washers clean best when matched with

specially formulated Hotsy detergents. More than 40 liquids and powders meet every cleaning need imaginable. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

> Looking to save time and money? See a Hotsy foamer in action!





OPTIONS:

8" Oil-Fired Draft Dampener prevents backdrafts and keeps cold air out.

Hotsy Accessories customize your application for top performance



washer; reduces overspray

and zebra striping

Distributed by:



www.Hotsy.com email:info@Hotsy.com P/N 8.914-210.0 Effective 8/12 Specifica to change without notice. ©2012 Hotsy Specifications & product descriptions subject A member of KÄRCHER North America

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ±5% of listed specifications.

Telescoping wands extend