



CW Premium Series

Industrial Cold Water
Pressure Washers

Electric — Portable — Belt Drive



CW-4004-1ME3

With up to 5000-PSI of cleaning power, this series of pressure washers is perfect for cleaning equipment inside commercial facilities. It can easily clean grit and grease.

PUMP

- External bypass system protects from heat build-up
- Factory preset unloader (CW-4004-1ME3 features Mi-T-M unloader)
- Forged brass manifold (Nickel plated on CW-4004-1ME3)
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

MOTOR

- Totally enclosed fan-cooled electric motor with thermal overload protection
- 10-foot power cord

FRAME

- Powder coated steel frame
- Totally enclosed belt guard
- 13-inch flat-free tires

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking high pressure hose
- 36-inch lance with insulated trigger gun (48-inch on CW-4004 and CW-5004 models)

LIMITED WARRANTIES

- 1 year Mi-T-M unloader (CW-4004-1ME3)
- 1 year electric motor
- 7 year General pump



CW Premium Series

Cold Water – Electric – Portable – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2405-4ME1	2400	4.6	7.5 HP, 230V, 1Ø, 32.0A	General	NEMA 6-50P	46x28x30in.	345 lb.	333 lb.
CW-2405-4ME3*	2400	4.6	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	NEMA L15-30P	45.5x32.5x30in.	355 lb.	343 lb.
CW-3004-4ME1	3000	3.5	7.5 HP, 230V, 1Ø, 32.0A	General	NEMA 6-50P	46x28x30in.	350 lb.	338 lb.
CW-3004-4ME3*	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	NEMA L15-30P	45.5x32.5x30in.	403 lb.	301 lb.
CW-3005-0ME1	3000	4.8	10.0 HP, 230V, 1Ø, 41.5A	General	NEMA 6-50P	45.5x32.5x30in.	470 lb.	396 lb.
CW-3005-0ME3*	3000	4.8	10.0 HP, 230V, 3Ø, 26.0A or 10.0 HP, 460V, 3Ø, 13.0A	General	NEMA 15-50P	45.5x32.5x30in.	450 lb.	376 lb.
CW-4004-1ME3*	4000	3.9	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	NEMA 15-50P	45.5x32.5x30in.	505 lb.	431 lb.
CW-5004-0ME3*	5000	4.0	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	NEMA 15-50P	45.5x32.5x30in.	505 lb.	431 lb.

*460V motors available as options.

ACCESSORIES AND OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0317	50-foot x ¾-inch non-marking hose – For when you need extra hose for added mobility	CW-5004-0ME3
851-0338	50-foot x ¾-inch non-marking hose – For when you need extra hose for added mobility	2400 to 4000-PSI models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 5100-PSI rated	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	2400 to 3000-PSI models
CX-0003	460V on 8.0-HP, 3Ø models – When 460V of power is available	CW-2405-4ME3 & CW-3004-4ME3
CX-0062	460V on 10.0-HP, 3Ø models – When 460V of power is available	CW-3005-0ME3
CX-0057	460V on 15.0-HP, 3Ø models – When 460V of power is available	CW-4004-1ME3 & CW-5004-0ME3
CX-0093	Stationary option – This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	CW-2405 & CW-3004 models
CX-0094	Stationary option – This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	CW-3005, CW-4004 & CW-5004 models



NEMA 6-50P,
50-amp plug



NEMA L15-30P,
30-amp plug



NEMA 15-50P,
50-amp plug



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.