

JCW Series

Cold Water – Gasoline – Belt Drive

Pump:

Equipped with the Mi-T-M Pressure Relief Start which eliminates pressure build-up in the system (3000, 3500 and 4000-PSI models) ■ Forged brass manifold ■ Thermal relief valve ■ Water filter with clear sleeve for screen inspection

Frame:

Powder coated steel frame and base plate with 1¼-inch tube handles ■ Convenient gun/wand holder and hose wrap ■ Two-piece belt guard for quick access to belts ■ 13-inch flat-free tires (10-inch on 2400, 2700 and 3000-PSI models)

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° ■ 50-foot x ¾-inch non-marking high pressure hose with quick connects ■ Professional-grade insulated trigger gun with safety lock-off

Limited Warranties:

1 year Mi-T-M unloader (3000, 3500 and 4000-PSI models) ■ 3 year Honda engine ■ 7 year AR pump

Certification:

Intertek - Certified to UL-1776

The longevity of a belt driven pressure washer makes the JCW Series the ideal choice for industrial cleaning jobs. It can handle tough and demanding cleaning jobs on construction sites, commercial cleaning sites and agricultural locations day in and day out.



JCW-3504-2MHB



MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JCW-2403-0MHB	2400	2.8	196cc Honda GX200 OHV	AR	3-0228	Adjustable pressure	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-2703-0MHB	2700	2.4	196cc Honda GX200 OHV	AR	3-0228	Adjustable pressure	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-3003-2MHB	3000	3.0	270cc Honda GX270 OHV	AR	3-0308	Mi-T-M, adjustable pressure	36in.	39.5x28.5x26in.	232 lb.	178 lb.
JCW-3504-2MHB	3500	3.7	389cc Honda GX390 OHV	AR	3-0308	Mi-T-M, adjustable pressure	48in.	39.5x28.5x26in.	249 lb.	195 lb.
JCW-4004-2MHB	4000	3.5	389cc Honda GX390 OHV	AR	3-0308	Mi-T-M, adjustable pressure	48in.	39.5x28.5x26in.	249 lb.	195 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0005	36-in. insulated dual lance	2400 to 3000-PSI models
851-0338	50-ft. x ¾-in. non-marking high pressure hose	All models	CX-0082	External bypass system - attaches to pump	3000 to 4000-PSI models
AW-8400-0021	Low pressure detergent injector	All models	CX-0085	External bypass system - attaches to base plate	3000 to 4000-PSI models