

Cold Water Gun and Wand Assemblies

Replaces your existing gun and wand assembly. Professional-grade insulated trigger gun with safety lock-off and quick connects. Wand assembly includes rubber grip and quick connects.



PART NUMBER	851-0095	851-0371	851-0309	851-0361
LENGTH	36in.	48in.	48in.	48in.
MAX. PSI	5000	5000	5000	7300
MAX. GPM	10.0	10.0	10.0	8.0
TEMPERATURE	120°F	120°F	120°F	120°F
INLET	3/8in.	3/8in.	3/8in.	3/8in.
MATERIAL	Stainless-steel	Stainless-steel	Powder coated black steel	Powder coated black steel

PRESSURE WASHERS

Hot Water Dual Lance Assemblies

Replaces your existing gun and wand assembly. Professional-grade insulated trigger gun with safety lock-off and quick connects. Adjustable pressure insulated dual lance.



PART NUMBER	850-0435	850-0436
LENGTH	36in.	48in.
MAX. PSI	5000	5000
MAX. GPM	10.0	10.0
TEMPERATURE	300°F	300°F
INLET	3/8in.	3/8in.
MATERIAL	Stainless-steel	Stainless-steel

Replacement Trigger Gun

16-0446

- Rated up to 5000-PSI
- 10.0-GPM flow rate



Hot water dual lance assembly, 850-0435