
# **HURRICANE FLIP**

- ✓ 2-in-1
- √ Versatile in use
- √ High precision rotor arm/rotor unit
- √ High quality swivel or toggle swivel
- √ Easy flip function







### **TECHNICAL DATA**

Pressure 4000 psi Temperature 250°F Inlet 3/8" NPTF






Important: Do not use unprotected!

# **FEATURES**

#### Flip function

Effortless turning of the wheels / 2-in-1 function. The Hurricane Flip can be converted from a floor cleaner to an undercarriage cleaner in just a few simple steps.

Part No. 80.9030 ø12" Part No. 80.9045 ø21"



# **HURRICANE FLIP Ø21" FEATURES**

### High quality swivel

DYF swivel with reinforced, self-lubricating stainless steel ball bearings and a carbide sealing system for high speed rotation.

Part No. 58.323

### High precision rotor arm

The rotor arm, which is manufactured in an automated welding process is robust and balanced.

Part No. 82.942 ø18.5"



# **HURRICANE FLIP Ø12" FEATURES**

# High precision rotor unit

DYF swivel with reinforced, self-lubricating bearings made from stainless steel and a carbide sealing for high RPM. New rotor arm design with low profile for cleaning jobs with limited clearance.

om r arm ee.

Part No. 58.913

### Toggle swivel

The proven toggle joint makes easy and efferotless cleaning possible. Positioned on the side of the housing, this special design enables cleaning under the vehicle.

Part No. 42.906



### **HP-Coupling**

The 1/4" quick coupler easily connects or disconnects the wand to the rotor unit for storage purposes or for use with other equipment.

Part No. 70.021 + 70.904



# **Hurricane Flip**

Name	Part No.	Ø	min. Clearance	Weight	Rotorarm	HP-Nozzles	HP- Gun	Stainless Steel Caster
HURF-300	78.607	12"	4"	11.7 lbs	2x 1/8" NPTF	2x 1503	1x	3x ø2½"
HURF-520	80.616	21"	5.7"	28.7 lbs	2x 1/8" NPTF	2x 1503	1x	3x ø2½"

Other nozzles sizes please order separately.