

- ✓ With fluid recovery port
- ✓ Ready to use
- ✓ Designed for higher pressures



The Graffiti remover has an upgraded swivel and rotor arm for more industrial applications such as graffiti removal. It is also used in restoring a wide variety of surfaces, as well as indoor and outdoor contract cleaning.



### TECHNICAL DATA

**Pressure** 5000 psi  
**Temperature** 250°F  
**Inlet** 3/8" NPTF



**FL-ABB 300**




**FL-ABB 200**

## FEATURES

### Recovery System

Environmental protection is more important than ever. These recovery units have a double wall housing to optimize vacuum power.

Residual water and debris can be recovered, recycled and reused.



### Rotor Arms

Can withstand up to 7300 psi, are precision welded and balanced.



### 2cw2 (2 Arms / 2 Nozzles)

Part No. 82.321 (ø 6") Part No. 82.323 (ø 10")

### Brush Ring

Ideal for outdoor applications such as concrete, brick, limestone or wood surfaces.



### Plastic rim guard

Indoor use, prevents dirt and debris from building up on the rim. Adheres to purity regulation in the food and clinical industries.

### Swiss Engineering

High rpm stainless steel swivel features reinforced self lubricated stainless steel ball bearings for improved performance. The dual spring based carbide seal system, guarantees long lasting operation under tough conditions.



### DYW Swivel

Part No. 55.020

Name	Part No.	ø	Weight	Swivel	Rotor Arm	HP-Nozzles	HP-Gun
<b>FL-ABB 200</b>	<b>78.285</b>	8"	6.0 lbs	1x DYW	2x 1/8" NPTF	2x 1503	1x
<b>FL-ABK 200*</b>	<b>78.286</b>	8"	6.2 lbs	1x DYW	2x 1/8" NPTF	2x 1503	1x
<b>FL-ABB 300</b>	<b>78.287</b>	12"	7.1 lbs	1x DYW	2x 1/8" NPTF	2x 1503	1x
<b>FL-ABK 300*</b>	<b>78.288</b>	12"	7.3 lbs	1x DYW	2x 1/8" NPTF	2x 1503	1x

\* with Plastic rim guard