

- √ pressure up to 4000 psi
- √ temperature up to 250°F
- √ complete stainless steel (INOX)
- √ quality swivel (DYF / maintenance free)
- √ quality rotor arm (balanced)
- \checkmark solid construction

Name	Part No.	ø	Weight	Rotor Arm	Nozzles	HP-Gun	Stainless Steel Wheels
TUW-520	80.611	21"	27.3 lbs	2x 1/8" NPTF	2x 1503	1x	2x ø 4" 1x ø 2¼"
TUW-750	80.612	30"	30.8 lbs	3x 1/8" NPTF	3x 1503	1x	2x ø 4" 1x ø 2¼"
TUW-520	80.613*	21"	33.3 lbs	2x Stabilizer	2x 0003	1x	2x ø 4" 1x ø 2¼"
TUW-750	80.614*	30"	36.2 lbs	3x Stabilizer	3x 0003	1x	2x ø 4"

Inlet: 3/8" NPTF

Mosmatic recommends using the guard plate with the TUW undercarriage cleaner.

TUW-520 Guard plate TUW-750 Guard plate Part No. 80.621 TUW-750 Guard plate



MOSMATIC Corporation BRISTOL, WI 53104-0400 USA | Phone: 1-800-788-9880 | www.mosmatic.com