## Specifications

MODEL	
Model #	157117
FLOW OUTPUT	
Pressure Rating	3500 psi
Flow Rate	3.5 gpm
Maximum Temperature	250° F
<b>DIMENSIONS / COMPONENTS</b>	
Length	59"
Width	35.625"
Height	43"
Weight (fueled)	548 lbs.
Pump Type	66DX
Engine Model	Honda GX390
Engine Type	Air-cooled 4-stroke
Drive	Direct
Burner	12 VDC
Engine Displacement	389cc
High Pressure Discharge Hose	3/8" x 50'
Chemical Injection Ratio	13 to 1
SUPPLIES REQUIRED (not included)	
Engine Fuel	Regular, Unleaded Gasoline (Capacity: 8 Gal.)
Engine Oil	See Engine Owner's Manual and Step 3 of the Assembly and Initial Set-up section for additional oil quantity needed due to oil drain hose.
Burner Fuel	#1 or #2 Diesel, B5 or lower Biodiesel, Kerosene, or Fuel Oil (Capacity: 8 Gal.)
Pump Oil (shipped with oil, but refills required)	SAE 30 non-detergent oil
Input Water Supply	Standard tap water @ 20-75 psi, delivered @ 4.2 gpm or higher
Input Water Supply Hose	Standard garden hose with inside diameter at least 5/8" (at least 3/4" diameter if hose longer than 100 ft.)
Battery	12 Volt, minimum 18 Amp/Hr. Lawn and Garden Battery (Group U1)