

A-Frame Hose Reels

Standard Features



- NyRim End Frames
- 325 Degree Max Temperature
- Friction Brake
- Heavy Duty Super Swivel®
- Lock Pin
- Rated at 4000 PSI
- Available in Gloss Black or SS

1/2" Plumbing

| | | |
|--------------------|-----------------|-----------------|
| Part Number | K01-0105 | K01-0106 |
| Description | 8" Painted | 12" Painted |

| | | |
|--------------------|--|---------------------|
| Part Number | | K01-0106-1 |
| Description | | 12" Stainless Steel |

1/2" Plumbing Totally Stainless Steel

| | |
|--------------------|----------------------|
| Part Number | K01-0106-1-SS |
| Description | 12" Stainless Steel |

- A-Frame reels come in 4 sizes 8 and 12 inches (see chart)
- A-Frame reels have pre-drilled mounting holes (ref I & H)
- Can be vertically mounted or horizontally mounted
- Totally Stainless Steel reels uses Mosmatic swivels
- Totally Stainless Steel reels can handle PH levels from 3-12



| | MODEL # | HOSE CAPACITY IN. FEET HOSE SIZE (I.D.) | | ALL DIMENSIONS IN INCHES | | | | | | | | | | APPROX. WT. LBS. | |
|--|---------------|---|------|--------------------------|-------|------|------|-----|---|------|------|--------|-----|------------------|------|
| | | SIZE | 3/8" | 1/2" | A | B | C | D | E | F | G | H | I | NET | SHIP |
| PAINTED REEL 1/2" PLUMBING | K01-0105 | 8" | 160' | 100' | 20.5 | 16.5 | 18.5 | 7.5 | 6 | 12.5 | 11.5 | 9.875 | 7.5 | 19 | 25 |
| | K01-0106 | 12" | 300' | 200' | 25.75 | 16.5 | 18.5 | 12 | 6 | 12.5 | 16 | 14.375 | 7.5 | 21 | 27 |
| | K01-0107 | 18" | 450' | 325' | 31.75 | 16.5 | 18.5 | 18 | 6 | 12.5 | 22 | 20.375 | 7.5 | 25 | 31 |
| | K01-0108 | 22" | 550' | 400' | 35.75 | 16.5 | 18.5 | 22 | 6 | 12.5 | 26 | 24.375 | 7.5 | 27 | 33 |
| STAINLESS STEEL REEL 1/2" PLUMBING | K01-0105-1 | 8" | 160' | 100' | 20.5 | 16.5 | 18.5 | 7.5 | 6 | 12.5 | 11.5 | 9.875 | 7.5 | 19 | 25 |
| | K01-0106-1 | 12" | 300' | 200' | 25.75 | 16.5 | 18.5 | 12 | 6 | 12.5 | 16 | 14.375 | 7.5 | 21 | 27 |
| | K01-0107-1 | 18" | 450' | 325' | 31.75 | 16.5 | 18.5 | 18 | 6 | 12.5 | 22 | 20.375 | 7.5 | 25 | 31 |
| | K01-0108-1 | 22" | 550' | 400' | 35.75 | 16.5 | 18.5 | 22 | 6 | 12.5 | 26 | 24.375 | 7.5 | 27 | 33 |
| TOTALLY STAINLESS STEEL REEL 1/2" PLUMBING | K01-0105-1-SS | 8" | 160' | 100' | 20.5 | 16.5 | 18.5 | 7.5 | 6 | 12.5 | 11.5 | 9.875 | 7.5 | 19 | 25 |
| | K01-0106-1-SS | 12" | 300' | 200' | 25.75 | 16.5 | 18.5 | 12 | 6 | 12.5 | 16 | 14.375 | 7.5 | 21 | 27 |
| | K01-0107-1-SS | 18" | 450' | 325' | 31.75 | 16.5 | 18.5 | 18 | 6 | 12.5 | 22 | 20.375 | 7.5 | 25 | 31 |
| | K01-0108-1-SS | 22" | 550' | 400' | 35.75 | 16.5 | 18.5 | 22 | 6 | 12.5 | 26 | 24.375 | 7.5 | 27 | 33 |