


Configuration	Skid			High cart			Low cart		
Name	640	640I	640IA	640	640I	640IA	640	640I	640IA
Model #	805-002	2419187	2418753	805-004	2419194	2419011	805-005	2419039	2419038
<b>Specifications</b>									
Gallons per minute	0.70 (2.6 LPM)	0.70 (2.6 LPM)	0.70 (2.6 LPM)	0.70 (2.6 LPM)	0.70 (2.6 LPM)	0.70 (2.6 LPM)	0.70 (2.6 LPM)	0.70 (2.6 LPM)	0.70 (2.6 LPM)
Maximum tip sizes	0.027"	0.027"	0.027"	0.027"	0.027"	0.027"	0.027"	0.027"	0.027"
Maximum pressure	3300 PSI (22.8 MPa)	3300 PSI (22.8 MPa)	3300 PSI (22.8 MPa)	3300 PSI (22.8 MPa)	3300 PSI (22.8 MPa)	3300 PSI (22.8 MPa)	3300 PSI (22.8 MPa)	3300 PSI (22.8 MPa)	3300 PSI (22.8 MPa)
Weight	36 lbs.	36.3 lbs.	36.5 lbs.	57 lbs.	57.3 lbs.	57.5 lbs.	57 lbs.	57.3 lbs.	57.5 lbs.
Maximum hose length	300'	300'	300'	300'	300'	300'	300'	300'	300'
Power	1.55 Hp Brushless motor, 120 V, 60 Hz, 11.8 A			1.55 Hp Brushless motor, 120 V, 60 Hz, 11.8 A			1.55 Hp Brushless motor, 120 V, 60 Hz, 11.8 A		
Generator requirement	5000 Watt (disable idle-down feature)			5000 Watt (disable idle-down feature)			5000 Watt (disable idle-down feature)		
<b>Features</b>									
Digi-Trac™	X	X		X	X		X	X	
IntelliSync®		X	X		X	X		X	X
ActivGuard™ GPS			X			X			X
<b>Included accessories</b>									
Spray gun	RX-Pro			RX-Pro			RX-Pro		
Spray hose	50' (15 m) P/N 316-505			50' (15 m) P/N 316-505			50' (15 m) P/N 316-505		
Spray filter	60 mesh, P/N 0089958			60 mesh, P/N 0089958			60 mesh, P/N 0089958		
<b>Literature</b>									
Operation manual (Form No. 805-911)	English / French / Spanish included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>			English / French / Spanish included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>			English / French / Spanish included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>		
Service manual (Form No. 2421885)	English / French / Spanish available online at <a href="http://www.titantool.com">www.titantool.com</a>			English / French / Spanish available online at <a href="http://www.titantool.com">www.titantool.com</a>			English / French / Spanish available online at <a href="http://www.titantool.com">www.titantool.com</a>		
RX-Pro manual (Form No. 0538801)	All languages included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>			All languages included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>			All languages included with product and available online at <a href="http://www.titantool.com">www.titantool.com</a>		
<b>Compliance</b>									
	Conforms to UL STD 1450 Certified to CAN/CSA STD C22.2 No. 68			Conforms to UL STD 1450 Certified to CAN/CSA STD C22.2 No. 68			Conforms to UL STD 1450 Certified to CAN/CSA STD C22.2 No. 68		
Radio Frequency Approvals	<p>Transmitter Frequency (all models): 2.4GHz                      Transmitter Power (all models): +8dBm                      NOTE: FCC/IC Notice (all models)                      Contains FCC ID: RYYEYSKBN                      Contains IC: 4398B-EYSKBN</p> <p>The enclosed device complies with Part 15 of the FCC Rules and with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:(1) this device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation.</p> <p>Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.</p> <p>This equipment is not granted protection against harmful interference and cannot cause interference on systems properly authorized.                      This equipment has the board BGM13P22A with homologation code ANATEL 01330-19-03402.</p>								