

WPX3100

GAS PRESSURE WASHER



Innovative. Efficient. Simple Operation.

WPX3100 GAS POWERED PRESSURE WASHER

INNOVATIVE. EFFICIENT. SIMPLE OPERATION.

Throughout every year, dirt, dust, and grime can build up on your home's siding, porch, foundation, and walkways. This buildup can be extremely difficult to remove by hand due to its stubbornness, compounded by the sheer amount of surface area that needs to be cleaned.



WHAT'S INCLUDED

- Owners manual
- Quick start guide
- 30ft high pressure hose
- Spray gun
- Spark plug wrench
- 10W30 Oil with funnel cap
- Soap tank/soap tube (pre-installed)
- 0°, 15°, 25°, 40° and Soap nozzles with nozzle cleaner



PRESSURE WASHER NOZZLES

The WPX3100 pressure washer comes with multiple nozzles, allowing you to adjust your spray in accordance with the material you're cleaning, such as concrete, brick, stone, wood, iron, and vinyl siding. The flexible hose and never-flat wheels ensure that you'll be able to easily reach any surface that needs a thorough washing, and its powerful engine is certain to get the job done.



RED 0° NOZZLE

Use to clean hard, embedded dirt & grime.
Use on concrete, brick, driveways, & patios.



YELLOW 15° NOZZLE

Use to clean paint, stain, mildew, oil, & stuck on dirt & grime. Use on wood, decks, home siding, driveways, & patios.



GREEN 25° NOZZLE

For general rinsing ideal for most all purpose cleaning such as home siding, brick patios, wood decks, driveways and sidewalks, garage floors, etc.



WHITE 40° NOZZLE

For delicate rinse & gentle cleaning of cars/trucks, boats, RV's patio furniture, lawn equipment, etc.



BLACK SOAP NOZZLE

Use to apply soap to cleaning surfaces in order to provide a thorough cleaning.

SPECIFICATIONS

PSI	3100
Flow (Gal/Min)	2.5
Engine	Westinghouse OHV
Engine Displacement (cc)	208cc
Engine Type	Horizontal Shaft
Low Oil Shutdown	No
Oil Capacity (oz)	20 oz
Oil Included	Yes
Recommended Oil	10W30
Fuel Capacity (G/L)	.9 G (3.3 L)
Fuel On/Off Switch	Yes
Starting Method	Recoil
Choke	Manual
Throttle Control	Automatic
Maximum Water Supply Temp (°F/°C)	140°F/60°C Max
Thermal Relief Valve	Yes
Easy Start Pump Valve	Yes
Pump Brand	Himore
Pump Type/Pump	Axial Cam/PW28-2.5
Pump Material Type	Brass
Wheel Size (DxW) (in.)	12 in x 2 in
Tire Type	Never Flat
Nozzles	0°, 15°, 25°, 40° & Soap
Max Outlet Pressure (psi/bar)	3600/248
Hose Length (ft)	30 ft
Hose Diameter (in/D)	5/16
Hose PSI Rating	3100
Hose Connectors	M22
Soap Tank	Yes
Soap Tank Capacity (G/L)	1 G (3.6 L)
Frame Construction	1-1/4" Steel Tubing
Emissions	CARB & EPA Compliant
Residential Warranty	3 Years
Commercial Warranty	1 Year
Dry Unit Weight (lbs/kg)	66 lbs (30 kg)
Shipping Weight (lbs/kg)	79 lbs (36 kg)
Unit Dimensions (L x W x H) (in/cm)	24 in x 19 in x 42 in (61 cm x 48 cm x 107 cm)
Box Dimensions (L x W x H) (in/cm)	27 in x 21 in x 24 in (69 cm x 53 cm x 61 cm)
UPC	853544008076
GTIN	00085354408076